## OPERATING MANUAL — SOLO MODELS

# ! IMPORTANT FOR END-USERS DO NOT THROW AWAY ! READ AND FOLLOW INCLUDED INSTALLATION GUIDE BEFORE USE

#### ONCE UNIT IS PLUGGED IN:

Turn on the unit by pressing the on/off button at the top of the vertical bar

You should start to feel some heat after a few minutes.

Units typically take 10-15 minutes to reach top operating temperature.

Leave unit on for at least 1-2 hours to dry and warm towels.

These units are safe to leave on 24/7

DO NOT PICK UP UNIT WHILE IN OPERATION: BARS WILL BE HOT



For additional control a seperate timer can be used: Leave the unit on and set your preferred windows of use — The timer will turn the unit on/off.

### THESE UNITS ARE DESIGNED TO HOLD 1-2 STANDARD TOWELS MAXIMUM: OVERLOADING OR EXCESSIVE OVERLAPPING MAY RESULT IN OVERHEATING

### **HOW TO FOLD YOUR TOWELS?**

Fold your towel in half length-wise or width-wise and then drape over the top bar. For best results, ensure towel covers all bars with minimal overhang. Note - for larger towels, they may need to be folded in thirds to fit.

### **HOW TO CLEAN YOUR HEATED TOWEL RACK?**

For best results, turn off unit and wait for it to return to room temperature, then wet a soft cloth with warm water and mild soap and wipe surface. Dry off with a soft, dry towel. Never use an abrasive cleaning pad or product as this could scratch the finish or paint. Stainless steel cleaner should not be used on any painted finish. Stainless steel cleaners can also be used on any of the stainless finishes.



WIDTH FOLD



