











WASHLET®

COMPARISON CHART

		G400	S550E	S500E	S350E	S300E
		MS920CEMFG (Elongated)	SW3056 (Elongated) SW3054 (Elongated classic)	SW3046 (Elongated) SW3044 (Elongated Classic)	SW583 (Round)	SW573 (round)
						
COLOR	COTTON (#01)	#01, #12	#01, #12	#01, #12	#01, #12	#01, #12
CLEANSE	REAR CLEANSE					
	SOFT REAR CLEANSE	●				
	FRONT CLEANSE					
	WIDE FRONT CLEANSE	—				
	OSCILLATING CLEANSE	●	●			
	PULSATING CLEANSE	—				
	INSTANTANEOUS WATER HEATING	—				
	WATER PRESSURE CONTROL	5 SETTINGS				
	WATER TEMPERATURE CONTROL	5 SETTINGS				
	WAND POSITION ADJUSTMENT	●				
AIR	AIR PURIFIER (DEODORIZER)	●				
	AIR DRYER	●				
	AIR TEMPERATURE CONTROL	5 SETTINGS				
SEAT	HEATED SEAT	●				
	TEMPERATURE CONTROL	5 SETTINGS				
	SoftClose SEAT AND LID	●				
SENSOR	SEAT SENSOR	●				
	AUTO OPEN / CLOSE LID	●	●	—	●	—
	AUTO FLUSH	●	—			
	NIGHT LIGHT	—	●	—	●	—
REMOTE CONTROL	REMOTE CONTROL	●				
	REMOTE CONTROLLED SEAT	●	●	—	●	—
	REMOTE CONTROLLED FLUSH	●	—			
HYGIENE	REMOVABLE LID	●				
	PREMIST*	●				
	EWATER+* FOR BOWL	—	●			
	EWATER+* FOR WAND	—	●			
	WAND CLEANING MODE	●				
	SELF-CLEANING WAND	●				
ENERGY SAVING	ENERGY-SAVER TIMER	3, 6, 9 HOURS				
	AUTO ENERGY SAVER	●				

wasHLET.+

*WASHLET+ is a seat and toilet system designed to conceal the supply connections. Please refer pages 64-99

NEW		NEW		
C200	C5	C100	C2	A100
SW2044 (Elongated)◆ SW2043R (Round)	SW3084 (Elongated)	SW2034 (Elongated)◆ SW2033R (Round)	SW3074 (Elongated)	SW2014 (Elongated)
				
#01, #12	#01, #12	#01, #12	#01, #12	#01
		•		
		—		
		•		
•		—	•	—
		—		
5 SETTINGS				
5 SETTINGS	3 SETTINGS	3 SETTINGS	3 SETTINGS	3 SETTINGS
		•		•
				—
5 SETTINGS	3 SETTINGS	3 SETTINGS		
•		—		
5 SETTINGS	3 SETTINGS	3 SETTINGS		
		•		
		—		
•		SIDE PANEL		
		—		
		—		
		•		•
				—
—	—	—	—	—
—	•	—	•	—
		•		
—	6, 9 HOURS	—	6, 9 HOURS	—
		•		

washL^{et}® + COMPARISON

ELONGATED		D-SHAPE		SQUARE
S550E	S500E	RW	RX	SW
SW3056(A)T40 SW3054(A)T40	SW3046(A)T40 SW3044(A)T40	SW4547(A)T60	SW4047(A)T60	SW4597AT60#01
				

CLEANSE	COLOR: Cotton (#01)	#01	#01	#01	#01	#01
	CONCEALED SUPPLY CONNECTION	•	•	•	•	•
	REAR CLEANSE	•	•	•	•	•
	SOFT REAR CLEANSE	•	•	•	•	•
	FRONT CLEANSE	•	•	•	•	•
	WIDE FRONT CLEANSE	•	•			
	OSCILLATING CLEANSE	•	•	•	•	•
	PULSATING CLEANSE	•	•	•	•	•
	INSTANTANEOUS WATER HEATING	•	•	•	•	•
	WATER PRESSURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS
	WATER TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS
	WAND POSITION ADJUSTMENT	•	•	•	•	•
AIR	AIR PURIFIER (DEODORIZER)	•	•	•	•	•
	AIR DRYER	•	•	•		•
	AIR TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	3 SETTINGS	5 SETTINGS
SEAT	HEATED SEAT	•	•	•	•	•
	HEATED SEAT TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS
	SOFTCLOSE SEAT AND LID	•	•	•	•	•
SENSOR	SEAT SENSOR	•	•	•	•	•
	AUTOMATIC OPEN AND CLOSE LID	•	•	•		•
	AUTOMATIC FLUSH	•*	•*	•*	•*	•*
	NIGHT LIGHT	•		•		•
REMOTE CONTROL	REMOTE CONTROL	•	•	•	•	•
	REMOTE CONTROLLED SEAT	•		•		
	REMOTE CONTROLLED FLUSH			•		
HYGIENE	REMOVABLE LID	•	•	•		•
	EWATER+® FOR BOWL	•	•	•		•
	EWATER+ FOR WAND	•	•	•	•	•
	PREMIST®	•	•	•	•	•
	WAND CLEANING MODE	•	•	•	•	•
	SELF-CLEANING WAND	•	•	•	•	•
ENERGY SAVING	ENERGY-SAVE TIMER	3, 6, 9 HOURS	3, 6, 9 HOURS	3, 6, 9 HOURS	6, 9 HOURS	6, 9 HOURS
	AUTO ENERGY SAVER	•	•	•	•	•

RATED POWER USAGE		1288W	1287W	1274W	1274W	1282W
LENGTH OF POWER CORD		Maximum length 4 ft.	Maximum length 4 ft.	Maximum length 2.95 ft	Maximum length 2.95 ft	Maximum length 2.95 ft
WAND FLOW RATE	REAR	9.1 - 14.5 oz. / min.	9.1 - 14.5 oz. / min.	9 - 14.1 oz. / min.	9 - 14.1 oz. / min.	9 - 14.1 oz. / min.
	SOFT	10.8 - 14.5 oz. / min.	10.8 - 14.5 oz. / min.	9 - 14.1 oz. / min.	9 - 14.1 oz. / min.	9 - 14.1 oz. / min.
	FRONT	9.8 - 14.5 oz. / min.	9.8 - 14.5 oz. / min.	10.2 - 14.1 oz. / min.	10.2 - 14.1 oz. / min.	10.2 - 14.1 oz. / min.
	WATER TEMP	86°F - 104°F	86°F - 104°F	95°F - 104°F	95°F - 104°F	86°F - 104°F
DRYER	AIR TEMP	95°F - 140°F	95°F - 140°F			95°F - 140°F
	AIR VOLUME	10.24 ft ³ / min.	10.24 ft ³ / min.	5.65 ft ³ / min.	5.65 ft ³ / min.	10.24 ft ³ / min.
HEATED SEAT	SURFACE TEMP	82° F - 97° F	82° F - 97° F	82° F - 97° F	82° F - 97° F	82° F - 97° F
WATER SUPPLY PRESSURE		7 psi - 109 psi	7 psi - 109 psi	7.25 psi - 109 psi	7.25 psi - 109 psi	7.25 psi - 109 psi
WATER SUPPLY TEMPERATURE		33°F to 95°F	33°F to 95°F	32°F - 95°F	32°F - 95°F	32°F - 95°F
AMBIENT TEMPERATURE		33°F to 104°F	33°F to 104°F	32°F to 104°F	32°F to 104°F	32°F to 104°F
SIZE	ELONGATED	15-5/16"W x 20-3/4"D x 3-15/16"H	15-5/16"W x 20-3/4"D x 3-15/16"H			
	D-SHAPE			1.27 ft x D 1.90 ft x H 0.48 ft	1.27 ft x D 1.90 ft x H 0.48 ft	
	SQUARE					1.28 ft x D 1.9 ft x H 0.35 ft

•* When installed with a compatible tank

