




Self-levelling adjustable pedestal supports all types of calibrated decking.




Versatile Head
Multiple options allow for deck joist widths of up to 100mm



Set Up 1
Allowing for joist widths of up to 51mm. Rotate until the fixing lugs meet the joist, then insert screws as required.



Set Up 2
A wider bearer joist of up to 80mm can be inserted in an alternative set up.



Set Up 3
Furthermore any joist width up to 100mm can be supported as shown, removing the 'snap-off' lugs as required. This also allows for double joist support.

Joist Lugs

- Holds joist in place
- Screw holes enable fixing of joist to head

Self-Levelling Bearer Support Head

- 'Ball and socket' joint concept allows a free moving captive head
- Provides slope correction of up to 10.5% (6°)
- No self-levelling shims required - see diagram.
- Can accommodate bearer width of up to 100mm.

Adjustable Threaded Section

Easily allows millimetre perfect adjustments within given range.

Height Extension Collar

- Easy to attach with a single 'click' motion
- Builds up pedestal height in 100mm increments

Wide Supporting Base

- Evenly spreads load
- Protects membranes
- Water drainage holes prevent moisture build-up
- Holes enable pedestals to be fixed to surface if required.

TECHNICAL SPECIFICATION

Material	PP Polypropylene (recyclable), UV resistant		
Biological/chemical	Resistant to moulds, algae, alkali, bitumen		
Height range	40-56mm	200-300mm	700-800mm
	50-70mm	300-400mm	800-900mm
	70-100mm	400-500mm	900-1000mm
	110-160mm	500-600mm	
	150-210mm	600-700mm	
Compression	2100kg (certified compression data available on request)		
Base Diameter	210mm / 220mm		
Head Diameter	135mm		
Bearer Capacity	Up to 100mm		
Working Temperature	-40°C to 120°C		