

OVAEDA® Composite Decking is manufactured from composition of wood flour and plastic, resulting in a material that has warmth and charm of wood without the drawbacks. Unlike timber decking, composite decking requires no treatment or staining.

- Long lasting: will not rot, warp or twist
- Non-slip and splinter-proof
- Low-maintenance: no need to treat or stain
- Manufactured from FSC® certified wood



Light Brown

Dark Brown

Light Grey

Dark Grey

### Woodgrain Boards

- Quick and simple to install
- Board dimension 142mm x 22m x 3m
- Joist spacing 350mm
- Hidden fixings available (screws included)
- Complete Encapsulation™ Technology
- 25 Year Warranty

### Accessories



Starter/End Clip

T-Clips

Bullnose Board



### Recommended System

We recommend decking is installed on a Tectonic® Aluminium Joist system.

	Test Method	Value		
Density	ASTM D792-13 Method B	1.19g/cm <sup>3</sup>		
Flexural Strength	ASTM D790-10 Procedure A	34.5 MPa		
Flexural Modulus	ASTM D790-10 Procedure A	3510 MPa		
Izod Unnotched Impact Strength	ASTM D4812-11	88 J/m		
Shore Hardness	ASTM D2240-05 (2010)	D/70/1		
Tensile Strength	ASTM D638-14	24.9 MPa		
Water Absorption	ASTM D570-98 (2010)	0.63%		
Coefficient of linear thermal expansion (1/C°)	ASTM D696-08	-30°C-30°C: 33.12x10 <sup>-6</sup>		
Slip Resistnace	Pendulum Test	Light Grey & Dark Grey	Light Brown & Dark Brown	
		Worst Dry	49	50
		Worst Wet	37	37
	Classification	Low risk of slip	Low risk of slip	
Reaction to Fire	EN ISO 13501-1	C <sub>fl</sub> - s1		

