

BLUambas® PROFIBUS

Function

The wireless system **BLUambas®** provides wireless data transmission in the fieldbus system PROFIBUS. Herewith mobile plant components or machines can be integrated simply into the system communication. For this reason BLUambas® is the perfect alternative for slip rings and trailing cables but without mechanic wear. As seen from the perspective of the controller the wireless system acts like a cable.

Instructions for use

BLUambas® for PROFIBUS ensures a transmission speed of up to 1,5 Mbps. To build up a PROFIBUS radio link one BLUambas® master module and at least one BLUambas® slave module are required. The maximum number of slave modules and PROFIBUS devices depends on the BLUambas® types.

BLUambas® is available with protection class IP20 or IP65 and can be freely selected within a radio link.

Variants

BLUambas® PROFIBUS Classic

A PROFIBUS radio link can be established between a master module and a maximum of one slave module. A maximum of four PROFIBUS devices can be installed behind the radio link and with up to 1.5 Mbps.

BLUambas® PROFIBUS Comfort

A PROFIBUS radio link can be established between a master module and a maximum of four slave modules. A maximum of four PROFIBUS devices can be installed behind the radio link and with up to 1.5 Mbps.

BLUambas® PROFIBUS Premium

A PROFIBUS radio link can be established between a master module and a maximum of eight slave modules. A maximum of four PROFIBUS devices can be installed behind the radio link and with up to 1.5 Mbps. In addition PROFIsafe communication can be transmitted.

Technical data

BLUambas® PROFIBUS (master+slave module):

- Transmission standard: IEEE 802.15.1 (Bluetooth)
- Transmission frequency: 2,4-2,4835 GHz
- Range indoor: 100m (depending on antenna)
- Range outdoor: 300m (depending on antenna)
- Antenna connection: SMA socket
- PB- refresh rate: 9,6kBit/s - 1,5MBit/s
- Temperature range: -20°C to 60°C
- PROFIBUS protocols: RS485 DPV0, DPV1

Version protection class IP 20:

- Installation: Top-hat rail
- Housing (H x W x D): 105 x 23 x 125 mm
- Voltage supply: 24 V DC, 2 W, terminal
- PROFIBUS interface: 9 pole Sub-D

Version protection class IP 65:

- Installation: 4 holes screw fastening
- Housing (H x W x D): 121 x 88 x 42 mm
- Voltage supply: 24 V DC, 2 W, M12 A coding
- PROFIBUS interface: M12 D coding



BLUambas® PROFIBUS IP20



BLUambas® PROFIBUS IP65

Ordering details	Art. No.
BLUambas® PROFIBUS Classic master module IP20	125100100
BLUambas® PROFIBUS Classic master module IP65	125100101
BLUambas® PROFIBUS Classic slave module IP20	125100102
BLUambas® PROFIBUS Classic slave module IP65	125100103
BLUambas® PROFIBUS Comfort master module IP20	125100104
BLUambas® PROFIBUS Comfort master module IP65	125100105
BLUambas® PROFIBUS Comfort slave module IP20	125100106
BLUambas® PROFIBUS Comfort slave module IP65	125100107
BLUambas® PROFIBUS Premium master module IP20	125100108
BLUambas® PROFIBUS Premium master module IP65	125100109
BLUambas® PROFIBUS Premium slave module IP20	125100110
BLUambas® PROFIBUS Premium slave module IP65	125100111

Accessories/antennas on request!