### **Convection Oven Spec Sheet**



KSS7002A / KSG7003A

FOTILE 24" Convection Oven meets all your demands for a built-in oven. With a wide temperature range from 104°F to 482°F, effortless one-touch operation, multifunctional 10 preset modes, 5 grill layers, and a 3D-Hot-Air Circulation System, the convection oven provides every home chef an opportunity to explore limitless culinary possibilities.





KSS7002A

### **Key Features:**



# 10 Preset Cooking Modes for Ease of Use

Baking, Grilling, Proofing, Defrosting & Much More




# Uniform Temperature for Accurate Cooking

Five Heating Tubes 3D-Hot-Air Circulation System Platinum-Alloy Temperature Sensor



KSG7003A



#### Professional Grade Glass Door

2 Layers of Low-E Glass+ 1 Layer of Tempered Glass Prevents heat loss from the oven and heat transfer to the door handle

### Other Features:

Easy to Clean

Touchscreen Operation

#### **FOTILE Contact Information:**

info@fotileca.com 1-844-315-0315 8365 Woodbine ave, Unit 113 Markham, ON L3R 2P4 ca.fotileglobal.com

## **Convection Oven Spec Sheet**





KSS7002A / KSG7003A





	KSS7002A	KSG7003A
Certification	ETL	ETL
Product Dimensions (WxHxD)(inch)	23 7/16 x 23 7/16 x 21 3/4	23 7/16 x 23 7/16 x 21 3/4
<b>Build-in Dimensions</b> (WxHxD) (inch)	Flush Built-in 23 9/16 x 23 9/16 x (≥22 7/8) Standard Built-in 22 1/16 x 23 1/4 x (≥21 11/16)	Flush Built-in 23 9/16 x 23 9/16 x (≥22 7/8) Standard Built-in 22 1/16 x 23 1/4 x (≥21 11/16)
Wattage (W)	3800	3800
Capacity (cu.ft.)	2.47	2.47
Power Supply (V/Hz)	220-240/60	220-240/60
Temperature Range (°F)	104 - 482	104 - 482
Preset Modes	10	10
Operation	Touchscreen	Touchscreen





## **Installation Examples:**













