

NovaCaddy Golf Trolley Remote Control Sync Process

Please follow steps below to sync remote with your NovaCaddy remote golf cart.

This is used to align the caddy frequency with an out-of-tune or replacement remote control or new control box.

For the remote with On/Off switch (no external antenna Pic1)

Step 1 - Make sure power is totally off for at least five (5) seconds

Step 2 - Hold down the stop button on the remote. DO NOT RELEASE THE STOP BUTTON FROM NOW, TILL THE WHOLE SYNC PROCESS COMPLETED.

Step 3 - Power up cart. Continue to hold down the stop button.

Step 4 - Continue hold down the stop button until the lights on the LED screen blink.

Step 5 - Cart is now in "sync" test each function to assure all are functioning.



Pic 1

For the remote with strap antenna (pic 2)

Step 1 - Make sure power is off for at least five (5) seconds.

Step 2 - Hold down the forward button on the remote. Make sure the red LED light is lit. DO NOT RELEASE THE FORWARD BUTTON FROM NOW, TILL THE WHOLE SYNC PROCESS COMPLETED.

Step 3 - Power up the cart. Continue to hold down the forward button on the remote.

Step 4 - Start counting slowly. Cart will start to move within 15-20 seconds.

Step 5 - Cart is now in "sync" test each function to assure they are functioning.



Pic 2