## 



NEMO

Material	Sto
Aluminium	PLS Key


Stock Finishes
PLS SEE COLOUR KEY CHART - Click for


	Guarantee
Link	5 Years

ntee	Installation
6	Vertical
	Horizontal

PRODUCT CODE	(mm)	Width (mm)	Sections	Pipe Centers	Wall to pipe Centers	Wall Distance	Nett Weight	Water Content	Fuel Type	Heat O	utputs
	Н	W	n	(mm) C1	A (mm)	D(mm)	(kg)	(It)		Watts	BTU
NMO 0280180003	1800	280	3	370	30-50	60-80	6.9	1.5	С	1252	4273
NMO 0375180004	1800	375	4	465	30-50	60-80	9.2	2.0	С	1670	5698
NMO 0470180005	1800	470	5	560	30-50	60-80	11.5	2.5	С	2087	7122
NMO 0470060005	600	470	5	560	30-50	60-80	4.5	0.7	С	846	2886
NMO 0660060007	600	660	7	750	30-50	60-80	6.3	1.1	С	1184	4040
NMO 0850060009	600	850	9	940	30-50	60-80	8.1	1.4	С	1522	5194
NMO 1040060011	600	1040	11	1130	30-50	60-80	9.9	1.7	С	1862	6353
NMO 1230060013	600	1230	13	1320	30-50	60-80	11.8	2.1	С	2200	7507
Please add finishing code								Fuel type	e i.e, C: Centr	al heating	

Please a	add finisr	ning code	Э
at the e	nd of the	product	code





Fuel type i.e., C: Central heating E: Electrical heating D: Dual heating (C+E)

A full range of made to order sizes available.

Please	ask	for	details	
110030	usk	101	uctums.	

Radiator width for made	
to order sizes	( n x 95 ) - 5 mm
n = number of sections	
Max. working pressure	10 bar
Max. working temperature	95 °C
Connections	1/2"
Section width	90 mm
Section depth	46 mm
Pipe center	C1 W + 90 mm