



TRI LEVEL HORIZONTAL BAR

#HBAR3

WARANTY:

Limited 10-year warranty on steel posts, welds, bars and other steel parts on all units that are fully welded, with non-moving parts. Limited 5-year warranty on steel posts, welds, bars and other steel parts for all units with moving parts.

PRODUCT SPECIFICATION:

TriActive USA's HBAR3 assumes three cross bars (5, 6, and 7 feet off ground on center) and four upright posts utilizing a slip fit tube that's welded inside the cross bars and drilling holes for 3/8" bolts to secure the cross bars in place. HBAR3 assumes usage of American standard size tubing, namely 3" x 3" square tubing x 11ga, 1-1/4" OD round tubing x 11ga, 1.5" Round Tube 11ga and 1/4" hot rolled flat bar. The part will have seven parts in total - 4 uprights and 3 cross bars. TriActive USA Fitness Equipment does not include any of the following: exposed cables, hydraulics or plastic seating.

POWDER COATING SPECIFICATION:

Powder coating thickness 6-8 mils. Coatings are tested for 1000 hours of salt spray resistance. Pre-treated, iron phosphate applied, zinc powder applied, functional powder applied, and final TGIC powder coat is applied to provide outstanding weathering capabilities.



*ACTUAL EQUIPMENT MAY LOOK DIFFERENT THAN SHOWN DUE TO FREQUENT DESIGN UPGRADES. THIS EQUIPMENT IS DESIGNED FOR INDIVIDUALS WEIGHING UP TO 330 LBS.



SAFE & SECURE



WEATHER RESISTANT



TAMPER RESISTANT

DIMENSIONS:
177" L X 8" W X 88" H

BAR HEIGHTS:
5FT, 6FT & 7FT

WEIGHT:
215 LBS

COLOR:
GREEN OR BLUE

ASSEMBLY:
NOT REQUIRED