



BOTTLESCREW JAW AND SWAGE STUD

CODE	THREAD SIZE	TO SUIT WIRE SIZE	L1 MIN	L1 MAX	H	A	PIN DIA	TDL KG
#SS-312TX-025	M5	3/32"	109	149	11.5	6	5	600
#SS-312T-020	M5	1/8"	109	149	11.5	6	5	600
*SS-312T-503	M5	1/8"	153	193	11.5	7	5	600
SS-312T-503M	M5	3mm	153	193	11.5	7	5	600
SS-312T-604	M6	5/32"	177	225	12.5	8	6	1000
SS-312T-635	M6	1/8"	167	207	12.5	8	6	1000
SS-312T-603M	M6	3mm	167	207	12.5	8	6	1000
SS-312T-845	M8	5/32"	200	260	15.5	11	8	1400
SS-312T-805	M8	3/16"	205	265	15.5	11	8	1400
SS-312T-948	M10	3/16"	235	295	17.5	13	9	2200
SS-312T-906	M10	3/16"	250	340	17.5	12.5	9	2200
SS-312T-126M	M12	6mm	290	380	28	14	12	4000
SS-312T-126	M12	1/4"	290	380	28	14	12	4000
SS-312T-128	M12	5/16"	310	390	28	13	12	4000
SS-312T-168	M16	5/16"	360	495	25	17	16	6500
SS-312T-1638	M16	3/8"	360	495	25	17	16	6500
SS-312T-1610	M16	10mm	360	495	25	17	16	6500
SS-312T-2038	M20	3/8"	425	560	28	20	20	850
SS-312T-2010	M20	10mm	425	560	28	20	20	8500
SS-312T-2012	M20	1/2"	435	600	28	20	20	8500
SS-312T-2012M	M20	12mm	435	560	28	20	20	8500
SS-312T-2414	M24	14mm	531	760	55	30	25	15000
SS-312T-2416	M24	16mm	551	780	55	30	25	15000

Indicates mini fittings, both mini bottlescrews are pressed with HEX3 dies.

* Available in economy range of fittings. Please consult our sales department for pricing.



Bridco have a large range of stainless steel rope fittings and connectors for an unlimited range of applications.