

YesColours®

PRODUCT NAME Acrylic Eggshell

ISSUE DATE 01/10/2023

PRODUCT DESCRIPTION

A water-based mid-sheen finish decorative emulsion that provides a durable, washable finish, resistant to condensation.

IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. YesColours will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use

SPECIAL PROPERTIES

Ease of use.
Quick drying.
Low Odour.

MAXIMUM VOC CONTENT (RFU)

0.11kgs/ltr

REGULATIONS / COMPLIANCE

2004/42 IIA WB (D) 150

COLOUR RANGE

White & All Colours. **Special colours can be matched by request*

PACKAGING

1ltr, 2.5ltr and 5ltr other pack sizes by arrangement.

COVERAGE

20 square metres per litre @ 25 microns dft

FLASHPOINT

X°C

STORAGE

Store between 5°C - 25°C. When not in use, cans must be kept sealed

SHELF LIFE

12 months from delivery date in original sealed containers

CLEANING

Ensure surfaces to be coated are dry and must be cleaned using the appropriate product to remove all traces of contaminants.

SURFACE PREPARATION

Please refer to our website for details on Surface Preparation.

HEALTH AND SAFETY

Refer to SDS and tin label prior to use.
Suitable respiratory equipment should be worn when spraying.

APPLICATION METHODS

	BRUSH	ROLLER	COMPLIANT SPRAY GUN	
MIXING RATIO	RFU	RFU	Base	1ltr
			Thinner	>10 %
THINNER OPTIONS			Water	
SPRAY GUN SETUP			1.2 - 1.4	
NUMBER OF COATS (GUIDE ONLY)	1-2 coats	1-2 coats	1-2 Coats	
FLASH OFF	15 mins between coats	15 mins between coats	15 mins between coats	
DRYING TIME	Touch dry 30mins @20°C Hard dry 24 hours	Touch dry 30mins @20°C Hard dry 24 hours	Touch dry 30mins @20°C Hard dry 24 hours	
RECOATABILITY / OVERCOATING	16hrs minimum, 14 days maximum	16hrs minimum, 14 days maximum	16hrs minimum, 14 days maximum	
WET FILM THICKNESS*	80 microns	80 microns	80 microns	
DRY FILM THICKNESS*	30 microns	30 microns	30 microns	

* YesColours Paints Ltd Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of YesColours' knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.