

# YesColours®

PRODUCT NAME Vinyl Matt Emulsion ISSUE DATE 17/3/2021 PRODUCT CODE DEC101

## PRODUCT DESCRIPTION

A premium quality water-based, flat matt emulsion for interior use on wall and ceiling surfaces, where a flat non-reflective finish is required.

## IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. YesColours will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak to our Technical Service Department on by contacting [hello@yescolours.com](mailto:hello@yescolours.com)

MAXIMUM VOC CONTENT (RFU) 0.005kgs/ltr

REGULATIONS / COMPLIANCE 2004/42 IIA WB (A) 30

COLOUR RANGE YesColours Collection 1 *\*Special colours can be matched by request*

COVERAGE 15 square metres per litre @ 25 microns dft

FLASHPOINT X°C

STORAGE Store between 5°C - 25°C. When not in use, cans must be kept sealed

SHELF LIFE 12 months from delivery date in original sealed containers

CLEANING Ensure surfaces to be coated are dry and must be cleaned using the appropriate product to remove all traces of contaminants.

SURFACE PREPARATION Please refer to our website for details on Surface Preparation.

HEALTH AND SAFETY Refer to SDS and tin label prior to use.

## APPLICATION METHODS

	BRUSH	ROLLER	HVLP	AIRLESS/AIR-ASSISTED
MIXING RATIO	RFU	RFU	Base Thinner 5 ltr > 10 %	Base Thinner 5 ltr > 10 %
THINNER OPTIONS	N/A	N/A	Water	Water
VISCOSITY	As supplied	As supplied	N/A	N/A
SPRAY GUN SETUP	N/A	N/A	Tip size 0.38mm Tip angle 65° Max press 138bar	Tip size 0.38mm Tip angle 65° Max press 138bar
NUMBER OF COATS (GUIDE ONLY)	1-2 Coats	1-2 Coats	1-2 Coats	1-2 Coats
DRYING TIME	Touch dry 1hr @ 20°C Hard dry 24 hrs	Touch dry 1hr @ 20°C Hard dry 24 hrs	Touch dry 1hr @ 20°C Hard dry 24 hrs	Touch dry 1hr @ 20°C Hard dry 24 hrs
RECOATABILITY (OVERCOATING)	4 hrs minimum	4 hrs minimum	4 hrs minimum	4 hrs minimum
WET FILM THICKNESS*	65 microns	65 microns	65 microns	65 microns
DRY FILM THICKNESS*	25 microns	25 microns	25 microns	25 microns

*\*YesColours Paints Ltd Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.*

*This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of YesColours Paints Ltd's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy.*