

Woodoc 50 Gloss & Matt Specification Sheet



Typical Application:

For exterior use where a clear, gloss or matt sealer providing a high build-up of product is required. Provides UV-protection and is water repellent. Ideal for yachts, boats, gates, garage doors, garden furniture and window frames. Not suitable for use on hard, dense wooden decks.

Product Features:

Woodoc 50 Gloss or Matt is a clear exterior sealer that enhances the natural appearance and colour of wood. The product provides excellent protection against ultra-violet radiation, wind, water, pollution and salt spray damage.

- Contains a special alkyd base that remains flexible preventing surface cracking associated with temperature variation.
- Ultra-violet radiation protection in extreme conditions.
- Suitable for all wood types.
- High-build characteristic for a smooth gloss or matt surface.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Does not affect glue.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

No: WD50 /001/EU

Dated: 22/08/12

Name:

Woodoc 50 - Exterior Gloss or Matt Sealer (Clear) (Marine)

Description:

Deep penetrating, clear, gloss or matt finish with UV- protection and water repellence, for outdoor use.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

By brush. Clean brush with White Spirits.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only white spirits.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, gloss or matt, high-build, exterior wood sealer. Formaldehyde-Free.

Wax Content: None.

Compatibility:

White Sprits.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

1 litre and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Europe: +44(0)1223 – 655 686

Email: info@woodoc.eu

www.woodoc.eu

Customer Service:

Tel (Office hours)

0800 228 9088 (UK), (1) 840 3969 (ROI)

+44 1223 655 686 (Europe)

Email: info@woodoc.eu or visit www.woodoc.eu