

Woodoc Water-Borne DECK Specification Sheet



Typical Application:

A water-borne exterior sealer, especially developed for application to all exterior wooden decks and -staircases, as well as other exterior wood.

Product Features:

Woodoc Water-Borne DECK creates a clear or tinted low-gloss finish.

- Excellent protection against wind, water, pollution and salt spray.
- The tinted product provides extra protection against ultra-violet radiation under extreme conditions.
- High build-up characteristic for a smooth and attractive low-gloss finish.
- Available in Clear, Oak, Mahogany, Teak and Imbuia.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish.
- Suitable for all types of wood.
- Non-toxic once dry.
- Does not affect glue.
- Wares naturally for easy maintenance.

No: WD WB DECK/001 Dated: 04/03/14

Name:

Woodoc Water-Borne DECK – Exterior Low-Gloss Sealer (Clear / Oak / Mahogany /Teak / Imbuia)

Description:

Provides low-gloss finish.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

Preferably by brush. Clean brush with water before dry.

Dilution:

Do not dilute product.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear or tinted, lead-free, exterior water-borne wood sealer. Formaldehyde-Free. NMP-Free.

Wax Content:

None.

Compatibility:

Water.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging: 1, 2,5 and 5 litres. (20 litres available on request)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Europe: +44(0)1223 – 655 686

Email: info@woodoc.eu

www.woodoc.eu

Customer Service:

Office hours +44(0)1223 655 686

Email: info@woodoc.eu or visit www.woodoc.eu