

# Woodoc 30 Specification Sheet



## Typical Application:

For exterior use where a clear, low-gloss sealer is required. Provides UV-protection and is water repellent. Ideal for doors, window frames, cladding, garage doors and wooden garden furniture. **Not suitable for use on decks.**

## Product Features:

Woodoc 30 is a clear exterior low-gloss sealer that enhances the natural appearance and colour of wood. The product is moisture repellent, has a wax fraction that feeds the wood, as well as a UV-absorber that protects the wood against the sun's rays.

- Protects exterior wood against seasonal and environmental moisture variation.
- Offers excellent protection against ultra-violet radiation.
- Enhances the grain and natural colour of the wood.
- Micro-porous once cured
- Suitable for all wood types.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Does not affect glue.
- Wares naturally for easy maintenance.

**No:** WD30/005/EU

**Dated:** 14/08/12

**Name:**

Woodoc 30 - Exterior Polymer and Wax Sealer (Clear)

**Description:**

Deep penetrating, clear, low-gloss finish with UV-protection and water repellence, for outdoor use.

**Coverage:**

First coat 10-12 m<sup>2</sup>/litre. Subsequent coats 12-14 m<sup>2</sup>/litre. 3 coats (average) 3,3 m<sup>2</sup>/litre.

**Application:**

By brush. Clean brush with white spirits.

**Dilution:**

Dilution is not recommended, but should dilution be necessary, use only white spirits.

**Drying Time:**

Drying will vary, depending on moisture and atmospheric conditions.

**Product Properties:**

Clear, low-gloss, exterior wood sealer.

Formaldehyde-Free

**Wax Content:** Low.

**Compatibility:** White spirits.

**Non-Compatibility:**

Acetone, Lacquer Thinners, Benzene and other solvents.

**Packaging:**

500 ml, 1 litre, 2,5 litres and 5 litres. (20 or 200 litres available on request from dealer)

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.**

**IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

European Distribution:

Woodoc Europe

Tel. +44 (0)1223 655 686 Fax +44 (0)1223 280 388

info@woodoc.eu

Customer Service:

Tel (Office hours)

0800 228 9088 (UK), (1) 840 3969 (ROI)

+44 1223 655 686 (Europe)

Email: [info@woodoc.eu](mailto:info@woodoc.eu) or visit [www.woodoc.eu](http://www.woodoc.eu)