

Technical Data Sheet for Fiberglass Warehouse Cloth Tape Roll

According to ISO 11014:2010

Date: 16 Mar-2024

Section 1: Description

Fiberglass cloth tape is made of twisted strands of fiberglass that are woven at right angles to one another. Cloth has the highest glass-to-resin ratio and strength of all fiberglass materials.

Fiberglass tape is usually a narrow, cloth strip with woven edges that prevent unraveling. Use this tape for reinforcing seams and corners, and over epoxy fillets on plywood stitch and glue boats. 6 oz/yd.

Section 2: Properties

Propertie	Value	Test Standard
Thickness	0.2 ± 0.02 mm	JC/T 174-2005
Weave	Plain	JC/T 174-2005
Warp Density	7.0 Ends/cm	JC/T 174-2005
Weft Density	7.0 Picks/cm	JC/T 174-2005
Roll Length	50 yards	JC/T 174-2005

The information herein is general information designed to assist customers in determining whether Fiberglass Warehouse products are suitable to their applications. Fiberglass Warehouse products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents and suitability for their specific applications. Nothing herein constitute any warranty express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.