

Material Safety Data Sheet

CS: 1.5.25

Page: 1 of 4

Infosafe No[™] LPZAI Issue Date :July 2015 ISSUED by Aldax Enterprises

Product Name **Aldax Crystal Cast Epoxy Casting Resin Part A**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name Aldax Crystal Cast Epoxy Casting Resin Part A
Company Name Aldax Enterprises Pty Ltd
Address 22A Hearne Street, Mortdale
 NSW 2223
Telephone Number Tel: (02) 9533 9555
Recommended Use Resin for coating systems.

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
 DANGEROUS GOODS.
 Hazard classification according to the criteria of NOHSC.
 Dangerous goods classification according to the Australia Dangerous Goods Code.
Risk Phrase(s) R36/38 Irritating to eyes and skin.
 R43 May cause sensitization by skin contact.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrase(s) S2 Keep out of reach of children.
 S24/25 Avoid contact with skin and eyes.
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 S61 Avoid release to the environment. Refer to special instructions/safety data sheet.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Bisphenol-A epoxy resin	25068-38-6	>60%
	C12-C14 Glycidyl ether	68609-97-2	10 - <30%
	Bisphenol F epoxy resin	9003-36-5	10 - <30%

4. FIRST AID MEASURES

Inhalation If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention.
Ingestion Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
Eye If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities Eyewash and normal washroom facilities
Other Information Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use carbon dioxide, dry powder, foam or water mist.
Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide.
Specific Hazards Combustible liquid. This product will readily burn under fire conditions.

CS: 1.5.25

Material Safety Data Sheet

CS: 1.5.25

Page: 2 of 4

Infosafe No[™] LPZAI Issue Date :July 2015 ISSUED by Aldax Enterprises

Product Name **Aldax Crystal Cast Epoxy Casting Resin Part A**

Hazchem Code +32
Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers.
Unsuitable Extinguishing Media Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill, slippery when spilled. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for Safe Storage Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids and bases, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC).
Biological Limit Values No biological limits allocated.
Engineering Controls Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.
Respiratory Protection If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection Wear gloves of Rubber, neoprene or PVC material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and

CS: 1.5.25

Material Safety Data Sheet

CS: 1.5.25

Page: 3 of 4

Infosafe No[™] LPZAI Issue Date :July 2015 ISSUED by Aldax Enterprises

Product Name **Aldax Crystal Cast Epoxy Casting Resin Part A**

Body Protection maintenance.
 Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Yellow clear liquid
Odour Mild odour
Melting Point Not available
Boiling Point >200°C
Solubility in Water Insoluble
Specific Gravity 1.10-1.15 at 25°C
pH Value Approx. 7 at 20°C
Vapour Pressure 0.01 Pa at 20°C
Vapour Density (Air=1) Not available
Flash Point >155°C
Flammability Combustible liquid
Auto-Ignition Temperature Not available
Flammable Limits - Lower Not available
Flammable Limits - Upper Not available

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions of storage and handling.
Conditions to Avoid Heat, flames and sparks.
Incompatible Materials Oxidizing agents, strong acids and bases
Hazardous Decomposition Products Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide.
Hazardous Polymerization Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information LD50 (Rat, Oral): >5000mg/kg
Inhalation Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Skin Irritating to skin. Skin contact will cause redness, itching and swelling. May cause sensitisation by skin contact.
Eye Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Chronic Effects Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persistence/Degradability May cause long-term adverse effects in the aquatic environment.

CS: 1.5.25

Material Safety Data Sheet

CS: 1.5.25

Page: 4 of 4

Infosafe No[™] LPZAI Issue Date :July 2015 ISSUED by Aldax Enterprises

Product Name **Aldax Crystal Cast Epoxy Casting Resin Part A**

Mobility Not available
Environ. Protection Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information This material is classified as a Class 9 (Miscellaneous Dangerous or Dangerous Goods according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
 Class 9 Dangerous Goods are incompatible in a placard load with any of the following:
 - Class 1, Explosives (when the class 9 substance is a fire risk substance),
 - Division 5.1, Oxidizing agents (when the class 9 substance is a fire risk substance), and
 - Division 5.2, Organic peroxides (when the class 9 substance is a fire risk substance).
U.N. Number 3082
Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (EPOXY RESINS)
DG Class 9
Hazchem Code +32
Packing Group III
EPG Number 9C1
IERG Number 47

15. REGULATORY INFORMATION

Regulatory Information Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.
 Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
Poisons Schedule S5
Hazard Category Irritant, Dangerous for the environment

16. OTHER INFORMATION

Date of preparation or last revision of MSDS MSDS created: July 2015

...End Of MSDS...

Copyright in the source code of the HTML, PDF, XML, XPO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
 The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.

CS: 1.5.25