

Material Safety Data Sheet

CSI 1.5.25

Page: 1 of 5

Infosafe No™ LPZAJ Issue Date : July 2015 ISSUED by Aldax Enterprises

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B
Company Name Aldax Enterprises Pty Ltd
Address 22A Hearne Street, Mortdale
 NSW 2223
Telephone Number Tel. (02) 9533 9555
Recommended Use Hardener for coating systems.

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
 DANGEROUS GOODS.
 Hazard classification according to the criteria of NOHSC.
 Dangerous goods classification according to the Australia Dangerous Goods Code.
Risk Phrase(s) R20/22 Harmful by inhalation and if swallowed.
 R34 Causes burns.
 R43 May cause sensitization by skin contact.
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrase(s) S2 Keep out of reach of children.
 S20/21 When using, do not eat, drink or smoke.
 S23(2) Do not breathe vapour.
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S28 After contact with skin, wash immediately with plenty of water
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 S60 This material and its container must be disposed of as hazardous waste.
 S61 Avoid release to the environment. Refer to special instructions/safety data sheet.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Benzoyl alcohol	100-51-6	30-50 %
	Trimethylenehexam ethylenediamine	25620-58-0	<20 %
	Isophoronediamine	2855-13-2	10-18 %
	Octahydro-4,7-met hano-1H-indenedim ethylamine	68889-71-4	<10 %

4. FIRST AID MEASURES

Inhalation If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin Remove all contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap for 15 minutes. Ensure contaminated clothing is washed before re-use or discard. Seek medical attention.
Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.
First Aid Facilities Eye wash fountain, safety shower and normal washroom facilities.
Advice to Doctor Treat symptomatically.
Other Information For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126) or a doctor at once.

CSI 1.5.25

Material Safety Data Sheet

CSI 1.5.25

Page: 2 of 5

Infosafe No™ LPZAJ Issue Date : July 2015 ISSUED by Aldax Enterprises

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use carbon dioxide, dry chemical, foam, water mist or water spray.
Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, nitrogen oxides.
Specific Hazards Combustible liquid. This product will readily burn under fire conditions.
Hazchem Code 2X
Decomposition Temp. >200°C
Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.
Other Information Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling Corrosive and combustible liquid. Attacks skin and eyes. May produce severe burns. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Avoid breathing in vapours, mist or fumes. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous. Prevent the build up of mists or vapours in the work atmosphere. Keep containers sealed when not in use.
Conditions for Safe Storage Corrosive and combustible liquid for storage and handling purposes. Keep tightly closed in a dry, cool, well-ventilated area, out of direct sunlight. Provide a catch-tank in a bunded area. Avoid sparks, flames and other ignition sources. Store away from incompatible materials. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the store-room reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids and AS 3780-2008 The storage and handling of corrosive substances. Reference should also be made to all Local, State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards No exposure standards have been established for the mixture by the National Occupational Health & Safety Commission (NOHSC). However, over-exposure to some chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels. As with all chemicals, exposure should be kept to the lowest possible levels.

CSI 1.5.25

Material Safety Data Sheet

CSI 1.5.25

Page: 3 of 5

Infosafe No™ LPZAJ Issue Date : July 2015 ISSUED by Aldax Enterprises

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B

Biological Limit Values No biological limits allocated.
Engineering Controls Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997: Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.
Respiratory Protection If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/particulate filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection Safety glasses with side shields, goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection Wear gloves of impervious material, such as PVC and neoprene. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear, colourless liquid.
Odour Amine like odour
Decomposition Temperature >200°C
Melting Point Not available
Boiling Point Not available
Solubility in Water Partly soluble
Specific Gravity 1.02
pH Value Not available
Vapour Pressure Not available
Vapour Density (Air=1) Not available
Flash Point >110°C
Flammability Combustible liquid
Auto-Ignition Temperature Not available
Flammable Limits - Lower Not available
Flammable Limits - Upper Not available
Dynamic Viscosity approx. 240 mPa.s at 25°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions of storage and handling.

CSI 1.5.25

Material Safety Data Sheet

CSI 1.5.25

Page: 4 of 5

Infosafe No™ LPZAJ Issue Date : July 2015 ISSUED by Aldax Enterprises

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B

Conditions to Avoid Extremes of temperature and direct sunlight. Heat and other sources of ignition. Protect from freezing.
Incompatible Materials Strong acids and strong oxidising agents.
Hazardous Decomposition Products Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.
Hazardous Polymerization Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Acute toxicity data for product:
 LD50 (Oral, Rat): 1500 mg/kg (calculated)
Inhalation Harmful by inhalation. Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion Harmful if swallowed. Ingestion of this product can cause irritation to the mouth, throat, oesophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.
Skin Ingestion of this product will cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.
Eye Causes burns. Corrosive to the skin. Skin contact can cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. May cause sensitisation by skin contact.
Chronic Effects Corrosive to eyes - contact can cause corneal burns. Contamination of eyes can result in permanent injury. Eye contact with vapour or liquid will cause stinging, blurring tearing, severe pain and possible permanent eye damage and blindness.
 Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals.

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persistence / Degradability Not available
Mobility Not available
Environ. Protection Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information This material is classified as a Class 8 (Corrosive Substances) Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).
 Class 8 Dangerous Goods are incompatible in a placard load with any of the following:
 - Class 1, Explosives
 - Division 4.3, Dangerous When Wet Substances
 - Division 5.1, Oxidising Agents
 - Division 5.2, Organic Peroxides
 - Class 6, Toxic or Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids
 - Class 7, Radioactive Substances
 and are incompatible with food and food packaging in any quantity.
 Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.
Marine Transport:
 Classified as Dangerous Goods by the criteria of the International Maritime

CSI 1.5.25

Material Safety Data Sheet

CSI 1.5.25

Page: 5 of 5

Infosafe No™ LPZAJ Issue Date : July 2015 ISSUED by Aldax Enterprises

Product Name Aldax Crystal Cast Epoxy Casting Resin Part B

U.N. Number Dangerous Goods Code (IMDG Code) for transport by sea.
 2735
Proper Shipping Name AMINES, LIQUID, CORROSIVE, N.O.S. - (CONTAINS: isophorone diamine, Trimethylenehexamethylenediamine AND Octahydro-4,7-methano-1H-indenedimethylamine)
DG Class 8
Hazchem Code 2X
Packing Group III
EPG Number 8A1
IERG Number 36

15. REGULATORY INFORMATION

Regulatory Information Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.
 Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
Poisons Schedule S5
Hazard Category Harmful, Corrosive

16. OTHER INFORMATION

Date of preparation or last revision of MSDS MSDS Prepared: July 2010

...End Of MSDS...

Copyright in the source code of the HTML, PDF, XML, XPS and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Aoshu Pty Ltd.
 Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Aoshu Pty Ltd.
 The compilation of MSDS's displayed is the intellectual property of Aoshu Pty Ltd.
 Copying of any MSDS displayed is restricted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Aoshu Pty Ltd.

CSI 1.5.25