



# Setting Up an Ideal 1X Chainline

OneUp Components

Crank type	Model numbers if applicable	1X Setup - Non-Boost	1X Setup - Boost
104mm BCD cranksets prior to 2009		104mm BCD with OneUp spacers in <b>wide</b> chainring position	Not possible
<b>Shimano</b>			
Shimano XTR 10-spd 2X (3X spaced 104mm BCD)	FC-M980	104mm BCD with OneUp spacers in <b>wide</b> chainring position	Not possible
Shimano XTR 10-spd 2X (2X spaced 88mm BCD)	FC-M985	88mm BCD Ring	Not possible
Shimano XT, SLX, Deore 10-spd 3X (104mm BCD)	FC-M780 FC-M670, FC-M610	104mm BCD with OneUp spacers in <b>wide</b> chainring position	Not possible
Shimano XT, SLX, Deore 10-spd 'compact' 3X (96mm BCD)	FC-M782, FC-M672, FC-M612	96mm BCD Ring with OneUp spacers in <b>wide</b> chainring position	Not possible
Shimano XT, SLX, Deore 10-spd 2X (2X spaced 104mm BCD)	FC-M785, FC-M675, FC-M677, FC-M615, FC-M617	104mm BCD with OneUp spacers in <b>narrow</b> chainring position	104mm BCD with OneUp spacers in <b>wide</b> chainring position
Shimano M8000/9000 50mm	FC-M8000, FC-M9000, FC-M9020	M8000/M9000 96mm BCD Ring	Not possible
Shimano M8000/9000 53mm ( <b>Boost</b> )	FC-M8000-B1, FC-M8000-B2, FC-M9000-B1, FC-M9000-B2	Not possible	M8000/M9000 96mm BCD Ring
<b>SRAM</b>			
SRAM XX1		SRAM Direct Mount Ring	SRAM Direct Mount <b>Boost</b> Ring
SRAM XX1 <b>Boost</b>		SRAM Direct Mount Ring	SRAM Direct Mount <b>Boost</b> Ring
SRAM <b>1X</b> X01, X1, GX w/ removable spider or Direct Mount Ring		SRAM Direct Mount Ring - or - 104mm or 94mm BCD with OneUp spacers in <b>wide</b> chainring position	SRAM Direct Mount <b>Boost</b> Ring
SRAM <b>1X</b> X01, X1, GX <b>Boost</b> w/ removable spider or Direct Mount Ring		SRAM Direct Mount Ring - or - 104mm or 94mm BCD with OneUp spacers in <b>narrow</b> chainring position	SRAM Direct Mount <b>Boost</b> Ring - or - 104mm or 94mm BCD with OneUp spacers in <b>wide</b> chainring position
SRAM <b>2X</b> XX		Not possible	120mm BCD ring
SRAM <b>2X</b> X0, X1/GX w/ removable spider		SRAM Direct Mount Ring - or - 104mm BCD with OneUp spacers in <b>narrow</b> chainring position	SRAM Direct Mount <b>Boost</b> Ring - or - 104mm BCD with OneUp spacers in <b>wide</b> chainring position
SRAM <b>2X</b> X0, X1/GX <b>Boost</b> w/ removable spider		SRAM Direct Mount Ring	SRAM Direct Mount <b>Boost</b> Ring - or - 104mm BCD with OneUp spacers in <b>narrow</b> chainring position
X1/GX non-removable spider		104mm or 94mm BCD with OneUp spacers in <b>wide</b> chainring position	Not possible
X1/GX <b>Boost</b> non-removable spider		104mm or 94mm BCD with OneUp spacers in <b>narrow</b> chainring position	104mm or 94mm BCD with OneUp spacers in <b>wide</b> chainring position
<b>Race Face</b>			
Race Face Cinch Direct Mount		RF Direct Mount Ring	RF Direct Mount <b>Boost</b> Ring
Race Face Cinch 2X spider		RF Direct Mount Ring - or - 104mm BCD with OneUp spacers in <b>narrow</b> chainring position	RF Direct Mount <b>Boost</b> Ring - or - 104mm BCD with OneUp spacers in <b>wide</b> chainring position
Race Face Cinch 3X spider		RF Direct Mount Ring - or - 104mm BCD with OneUp spacers in <b>wide</b> chainring position	RF DM Boost Ring
Race Face Non-Cinch		104mm BCD with OneUp spacers in <b>wide</b> chainring position	Not possible