



## FEATURES

- Special switching power supply designed for professional laser galvanometer industry
- Universal 165 - 264VAC or 180 - 370VDC Input voltage
- Operating ambient temperature range: -30°C to +70°C
- Low ripple & noise
- High I/O isolation test voltage up to 3000VAC
- Operating altitude up to 5000m
- Output short circuit, over-current, over-voltage protection
- Design refer to IEC/UL62368-1, EN60335-1, EN61558-1, GB4943.1

LM90-12A15 series is one of Mornsun's dual output non-isolation enclosed AC-DC switching power supply. It features universal AC input and at the same time accepts DC input voltage, cost-effective, high efficiency, high reliability and double or reinforced insulation. These converters offer excellent EMC performance and meet IEC/EN61000-4, IEC/UL/EN62368, GB4943 standards and they are not only specific used in the laser galvanometer industry, but also widely used in current sensors, motors and other fields.

## Selection Guide

Certification	Part No.	Output Power (W)	Nominal Output Voltage and Current (Vo/Io)		Output Voltage Adjustable Range (V)	Efficiency at 230VAC (%) Typ.	Max. Capacitive Load (μF)	
			(Vo1/Io1)	(Vo2/Io2)			Vo1	Vo2
EN/BIS/BS	LM90-12A15	90	+15V/3.0A	-15V/3.0A	14.25-15.75	82	5000	3000

## Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range	AC input	165	--	264	VAC
	DC input	180	--	370	VDC
Input Voltage Frequency		47	--	63	Hz
Input Current	230VAC	--	--	2	A
Inrush Current	230VAC Cold start	--	60	--	
Leakage Current	240VAC	<0.75mA			
Hot Plug		Unavailable			

## Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	Full load range	Vo1	±1.0	--	
		Vo2	±3.0	--	
Line Regulation	Rated load	Vo1	±1.0	--	%
		Vo2	±3.0	--	
Load Regulation	0% - 100% load (Balanced load)	Vo1	±1.0	--	
		Vo2	±3.0	--	
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	Vo1	100	--	mV
		Vo2	100	--	
Temperature Coefficient		--	±0.03	--	%/°C
Minimum Load	Vo1	--	10	--	%
Start-up Delay Time	Rated load	--	--	3.0	s
Hold-up Time	230VAC	20	--	--	ms
Short Circuit Protection	Recovery time <3s after the short circuit disappear.	Hiccup, continuous, self-recover			
Over-current Protection	Dual output with balanced load	110% - 200% Io, self-recover			

Over-voltage Protection (Vo1)	<22VDC (Hiccup, self-recover)
Note: *The "Tip and barrel method" is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor, please refer to enclosed Switching Power Supply Application Notes for specific information.	

## General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Isolation Test	Input - output	3000	--	--	VAC	
	Input - ⊕	1500	--	--		
	Output - ⊕	500	--	--		
Insulation Resistance	Input - output	50	--	--	MΩ	
	Input - ⊕	50	--	--		
	Output - ⊕	50	--	--		
Operating Temperature		-30	--	+70	°C	
Storage Temperature		-40	--	+85		
Storage Humidity	Non-condensing	10	--	95	%RH	
Operating Humidity		20	--	90		
Power Derating	Operating temperature derating	+50°C to +70°C	2.5	--	--	%/°C
Safety Standard		IS13252 (Part1) safety approved & EN62368-1, BS EN 62368-1(Report) Design refer to IEC/UL62368-1, EN60335-1, EN61558-1, GB4943.1				
Safety Class		CLASS I				
MTBF	MIL-HDBK-217F@25°C	>300,000 h				



## Mechanical Specifications

Case Material	Metal (AL1100, SGCC)
Dimensions	129.0 x 97.0 x 30.0 mm
Weight	305g (Typ.)
Cooling Method	Air cooling



## Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032	CLASS A	
	RE	CISPR32/EN55032	CLASS A	
	THD	IEC/EN61000-3-2	CLASS A	
Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	perf. Criteria A
	RS	IEC/EN61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN61000-4-4	±2KV	perf. Criteria A
	Surge	IEC/EN61000-4-5	line to line ±1KV/line to ground ±2KV	perf. Criteria A
	CS	IEC/EN61000-4-6	10 Vr.m.s	perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	0%, 70%	perf. Criteria B

Product Characteristic Curve




Note: This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.



Dimensions and Recommended Layout

# AC/DC 90W Enclosed Switching Power Supply LM90-12A15

# MORNSUN®



**Note:**

- For additional information on Product Packaging please refer to [www.mornsun-power.com](http://www.mornsun-power.com). Packaging bag number: 58220120;
- Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75% RH with nominal input voltage and rated output load;
- The room temperature derating of 5°C/1000m is needed for operating altitude greater than 2000m;
- All index testing methods in this datasheet are based on our company corporate standards;
- In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
- We can provide product customization service, please contact our technicians directly for specific information;
- Products are related to laws and regulations: see "Features" and "EMC";
- The out case needs to be connected to PE (⊕) of system when the terminal equipment in operating;
- The output voltage can be adjusted by the ADJ, clockwise to decrease;
- Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

## Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China  
 Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com

# MORNSUN®

MORNSUN Guangzhou Science & Technology Co., Ltd.