



quince&co.

errata

---

## Sophie

Pam Allen

pg 2 / column 2

Cable panels (over 14 sts)

Note: Side and center cables are identical, but they begin at the neck on different rows to stagger them. Hence, cable crossings are worked on different rnds. Cable panel begins and ends on 9 sts, but stitches are added on first crossing row and subtracted on last crossing row.

Center cable

Rnds 1-8: Knit.

Rnd 9: Sl 4 sts to cn and hold in front, k10, k4 from cn.

Rnds10-16: Knit.

Rnd 17: K6, sl 4 to cn and hold in front, k4, k4 from cn.

Rnds 18-30: Knit.

Rep Rnds 9-30 for Center cable.

Side cables

Rnds 1-16: Knit.

Rnd 17: Sl 4 sts to cn and hold in front, k10, k4 from cn.

Rnds18-24: Knit.

Rnd 25: K6, sl 4 to cn and hold in front, k4, k4 from cn.

Rnds 26-30: Knit.

Rep Rnds 9-30 for Side cables.

pg 4 / column 2

fourth paragraph from top

Cont even as established until pc meas 12½" [32 cm] from underarm and at the same time on **fourth** full repeat of cable pattern (**one full repeat is Rows 9-30**), work dec's across cable pattern on Rnds 9 and 17 of center and side cables as follows: