

Litonet Pro

HIGH VISCOSITY LIQUID CLEANER FOR THE REMOVAL OF HALOS AND CONSOLIDATED EPOXY GROUT RESIDUE FROM ALL TYPES OF CERAMIC, PORCELAIN AND MOSAIC TILES. EFFECTIVE IN REMOVING GRAFFITI, SPRAY PAINTS AND INK. BREAKS DOWN SILICONE CAULK RESIDUE.



DESCRIPTION

Litonet Pro is a liquid cleaner with an alkaline pH ideal for the removal of catalysed epoxy residue, even a long time after grouting, from all types of ceramic and porcelain tiles, including delicate surfaces such as honed ceramics, vitreous or ceramic mosaics, natural stones.

Thanks to its high viscosity, Litonet Pro is ideal for cleaning interior and exterior walls and floors.

ADVANTAGES

- Non-aggressive solution, which can also be used on polished marble and honed or polished stoneware without the risk of corrosion or tarnishing
- Versatile and usable on all surfaces
- Effective also on halos catalysed for some time
- The dense and viscous formula also facilitates vertical application

PACKAGING

0.5 l bottles (boxes with 12 pcs)

FIELDS OF APPLICATION

The pure cleaner, thanks to its excellent dissolving properties, is particularly effective in removing halos and consolidated residue of epoxy grouts such as Starlike® EVO, Starlike® Crystal EVO, Starlike® ColorCrystal EVO, EpoxyÉlite EVO and EpoxyÉlite EVO FR, even on hard-to-clean materials such as thin pressed or compacted slabs, also with wood effect and micro-groove surfaces.

Thanks to its formulation, it is gentle on materials without instigating corrosion.

Also ideal for the removal of graffiti, spray paints and ink.

Effective in removing silicone residue and halos produced by organic polymers.

APPLICATION

Shake well before use.

For the removal of epoxy grout halos or residue, the detergent must be applied once the grouting has totally set (normally after 5 days at a temperature of +20/+25°C).

For fresh residue the product requires less time to work, while for more consolidated residue, the product will need to be left in contact for longer.

Apply the pure, undiluted product directly onto the affected surface, spreading it evenly using a special pad or brush. Let the product work for as long as needed, from about 10 to 30 minutes depending on how much residue needs to be removed.

Then rub the surface with white felt (art. 109GBNC) or using a single disc machine with a white disc pad for larger surfaces.

It is recommended to mechanically rub the product when applied to facilitate its removal.

Collect the cleaning solution using a sponge, rubber squeegee broom or wet vacuum cleaner.

Finally, rinse well with clean water and dry with a clean rag or cloth.

Do not wait for the rinse water to evaporate as this may cause halos to reappear on the surface.

If epoxy grout residue can still be seen after rinsing, repeat the application following the same procedure.

WARNINGS

- Spread the product at temperatures between +5°C and +35°C
- The product is corrosive. Wear protective clothing during handling. Follow the instructions shown on the label and safety sheet
- Before use, protect doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and all surfaces that may be damaged by direct contact with the detergents

- Change the rinse water frequently
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
- Shake well before use
- On honed stoneware, do not let the product work for more than 10 min. In any case, it is recommended to perform a spot test to check for any possible tarnishing
- Do not use to remove thick epoxy grout residue. In this case use Litostrip
- Do not use the product for applications not stated in this technical sheet
- If in doubt, contact the Litokol S.p.A Technical Help Service.

SAFETY INFORMATION

Consult the product safety data sheet, available on request.
PRODUCT FOR PROFESSIONAL USE

IDENTIFICATION DATA

Appearance	Thick liquid
Colour	White
Odour	Feature
Customs code	34029090
Shelf life	24 months in original packaging away from sources of heat and direct sunlight. Protect against frost.

APPLICATION DATA

Treatment time	10 - 30 minutes
Flammable	NO
pH	11,5 - 12,5
Specific gravity	1,12 kg/l
Application	Sponge or white felt
Application temperatures	From +5°C to +35°C
Consumption	4 - 6 m ² /l

NOTES

Data detection at temperature +23 °C, R.H. 50% and with no wind. May vary depending on the specific conditions of the installation site.

Data Sheet **n. 323**
Revision **n. 4**
Date: **January 2021**

The information and provisions contained in this technical data sheet reflect our best experience. Given the impossibility of directly intervening on the conditions of the work site and execution of the works, they represent indications of a general nature, which are in no way binding on our Company. It is therefore advisable to perform a spot test to check the suitability of the product for the intended use. In any case, users must determine whether or not it is suitable for the intended use and shall assume all associated responsibility.

Litokol S.p.A.
Via G. Falcone 13/1
42048 Rubiera (RE) Italy
Tel. +39 0522 622811
Fax +39 0522 620150
info@litokol.it

www.litokol.it

