

Copper Foil Paper-Wax 400V

μF	Voltage	Diameter		Length		Cat. No.
		Inches	mm	Inches	mm	
0.10	400V	0.563	14.3	1.000	25.4	PH9004-4104J
0.22	400V	0.562	14.3	1.313	33.3	PH9004-4224J
0.33	400V	0.750	19.1	1.313	33.3	PH9004-4334J
0.39	400V	0.750	19.1	1.313	33.3	PH9004-4394J
0.47	400V	0.813	20.6	1.375	34.9	PH9004-4474J
1.0	400V	1.063	27.0	1.875	47.6	PH9004-4105J
1.5	400V	1.063	27.0	2.063	52.4	PH9004-4155J
2.2	400V	1.313	33.3	2.125	54.0	PH9004-4225J
3.3	400V	1.750	44.5	2.125	54.0	PH9004-4335J
3.9	400V	1.750	44.5	2.500	63.5	PH9004-4395J
4.7	400V	1.875	47.6	2.500	63.5	PH9004-4475J

Tolerance: +/- 5%

Operating Temperature: 80°C

Voltage: 400VDC

Dielectric: Paper & Wax

Pure Copper Foil – CDA-10

Lead wire: 99.99% Silver

0.1uf - 0.39uf = 20awg solid

0.47uf - 2.2uf = 18awg solid

3.3uf and up = 3x20awg

RoHS Compliant

Made in USA

