



# Hydro Primer HS™

## Penetrating Roof Primer

### Product Description

ENCO® Hydro Primer HS™ is a professional Ultra-Premium Quality, high solids 100% acrylic penetrating roof primer for newly sealed or previously sealed concrete roofs. Its high solids (>32%) and small particle size formulation guarantees acrylic polymer will penetrate and seals internal cracks and pores to water-proof roofs when used with elastomeric sealers

### Product Uses

Proven waterproofing properties on horizontal roof and vertical wall applications. suitable for:

- Asphaltic Roofing Membranes
- Concrete
- Polyurethane Foam
- Aged Galvanized Metal and Wood

### Advantages

- Seals cracks and water proofs
- Polymer formulated
- Expand and contracts with the structure
- Low VOC content (<100 g/L)

### Packaging Sizes

Available in 5-gal pail.

### Product Characteristics & Properties

Coverage	Approximately 100 Square feet per gallon <i>Depending on surface texture, porosity and application method</i>
Shelf Life	18 Months unopened
Weight per Gallon	8.8 ± 5%
Storage Temperature	75-85°F
Disposal	Consult local and federal agencies for details

### Surface Preparation

1. Clean - Pressure wash roof with a mild detergent and rinse thoroughly. Remove all dirt, grease and loose particles such as gravel, previous coatings, etc., and kill and remove any mildew or fungus with a bleach solution.
2. Repair - Repair concrete cracks and holes using an elastomeric crack filler

### Product Application

Apply a first coat using a roller, brush or airless sprayer. Apply only at temperatures above 50°F. Do not apply if roof surface temperature is above 95°F. If roof is too hot, spray with water to avoid sealer from drying up too quickly. Do not apply after 4 PM. Do not apply if rain is forecast within 24 - 48 hours. Allow at least 4 hours of drying time. **DO NOT THIN OR DILUTE FROM FULL STRENGTH**

### Caution

Contains acrylic resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. If swallowed, do not induce vomiting. CONSULT A PHYSICIAN IMMEDIATELY. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN. Refer to the product's safety information on the Safety Data Sheet (SDS).

### Limitation of Liability

Our liability regarding this product is limited to its replacement or its refund value should it not comply with our specifications and does not include any application costs.

### Contacts

For additional information please contact Enco® Manufacturing Corp.