



PVA + PRIMER™

Drywall Primer

Product Description

ENCO® PVA+ PRIMER™ is a latex primer for new or uncoated drywall (gypsum board) panels on ceilings, walls and trim. Formulated to meet the performance requirements of professional applicators. PVA+ PRIMER™ dries in 30 minutes, presents an excellent hiding film that seals and primes surface to lessen the quantity of topcoats needed to provide a consistent, high-quality finish, enhancing paint adhesion and increasing paint overall yield. May be applied with brush, roller or spray.

Product Features

- Seals pores of new or uncoated drywall.
- Promotes adhesion of all paints.
- For interior use on wall and ceiling panels
- Fast drying
- Low V.O.C

Product Characteristics & Properties

Vehicle Type	Latex
Coverage	Up to 400 Sq. Ft./Gal on smooth surfaces. Rough, porous or textured surfaces: up to 300 Sq. Ft/Gal <i>May vary depending on application methods</i>
Mils	1.5 - 2
Gloss / Sheen	Flat (1-5%)
Shelf Life	18 Months unopened
VOC (Volatile Organic Compounds)	< 100 g/L
Viscosity	90-100 Ku's
Appearance	White
Solids by Weight	52 ± 5%
Solids by volume	35 ± 5%
Drying Time	30 min. to touch / 2 hrs. to recoat
Clean Up	Clean water and soap
Weight per Gallon	11.35 ± 5%
pH	8.5 – 9.0
Storage Temperature	75-85°F
Disposal	Consult local and federal agencies for details

Surface Preparation

1. Patch: Patch all holes and cracks with traditional gypsum board materials and methods.
2. Wipe: Wipe or blow surfaces to remove any joint compound remaining dust. Let dry panel prior to primer application.



Product Applications

Stir thoroughly before using.

Paint always on shaded side of the building. Do not dilute paint, use as supplied. Do not apply when surface or air temperature is below 50°F or if rain is expected within 5 hours. Apply product generously with brush, roller or sprayer. Avoid excessive brushing or spreading too thinly. If you use a roller, we recommend a synthetic cover.

This product will perform as specified if the instructions on this label are followed for the preparation and application on surfaces.

Caution

Close the container tightly after using and **KEEP AWAY FROM THE REACH OF CHILDREN**. Refer to the SDS to obtain additional safety details before starting to use this product

First Aid

If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty in breathing, eye watering, headache or dizziness, leave the area to obtain fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. If continued difficulty is experienced, get medical assistance immediately

WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Contacts

For additional information please contact Enco® Manufacturing Corp.

Limitation of Liability

The product warranty is limited only to its replacement or refund value of the product should not comply with our specifications and does not include application costs. For any claims, customer must present original proof of purchase.