

# ULTRA™ QUICK START GUIDE

## INFLATING AND DEFLATING







CLOSED / UP POSITION



OPEN / DOWN POSITION

#### **INFLATION**

\*ULTRA™ boards are compatible with both the iROCKER Electric Pump and Hand Pump

## E-PUMP

- Before connecting the hose, make sure the inflation valve is in the CLOSED/UP position.
- Connect the hose to the inflate valve to begin inflating.
- Set the electronic pressure gauge to the PSI recommended on the valve and press start; once that PSI is reached, the pump will automatically stop and you can enjoy your new favorite product, hassle free.
- Check the recommended pressure (PSI)

  as shown on the valve flange around your
  product's inflation valve.
- Connects via car power outlet or alligator clips directly to a 12V battery. The iROCKER Portable Battery (sold separately) provides another option.

## 🕕 HAND PUMP

- Before connecting the hose, make sure the inflation valve is in the CLOSED/UP position.
- Connect the hose and set the pump to **SETTING 1**, then begin inflating.
- The pump's pressure gauge will not register until the board reaches the PSI indicated on the left side of the scale of the pump gauge.
- Midway through inflation, when pumping becomes more difficult, set the pump to **SETTING 2** and continue inflating.
- When nearing full inflation, set the pump to SETTING 3 and fill to the maximum PSI recommended on the valve.

## **DEFLATION**

\*All inflatable iROCKER products can be deflated with an electric/hand pump. Connect the hose to the deflate valve to begin deflating. E-Pump - Set to AUTO, turn off by pressing AUTO again when the product is completely deflated.

Hand Pump - Manually deflate the product until no air is left inside.

## E-PUMP & HAND PUMP

- 1 Make sure the air valve is **DRY**.
- Press firmly on the pressure release pin for 2 seconds, then twist to lock into the OPEN/DOWN position.

## A Be

Be prepared for a loud rush of air when opening the air valve.



#### FIN INSTALLATION



OPEN/UP POSITION



ALIGNED WITH NOTCH



CLOSED/DOWN POSITION





INSERT TETHER LOCK / ROTATE TO LOCKED POSITION

- Make sure the fin box lock is in the OPEN/UP position.
- Insert the front of the fin into the notched section of the fin box. Rock the fin back and down until it's in place, then set the fin lock lever to the CLOSED/DOWN position.
- Confirm each fin is securely attached before paddling.
- Insert the tether-lock into the fin.
- Turn toward the locked icon until it snaps into position.
- To release the tether, turn toward the unlocked icon and remove the tether.



## ULTRA™ QUICK START GUIDE

### FOLDING YOUR ULTRA™ BOARD

\* Your ULTRA™ inflatable paddle board can be folded the traditional single-fold way, or double folded to make it extra compact and fit into your ULTRA™ backpack.

## (1x) SINGLE FOLD


- Once the board is completely dry and fully deflated, lay it deck-side up on a flat surface.
- Begin folding the board tightly in sections, starting from the nose.
- Continue folding until the board is completely (3) rolled up, then set the air valve to the CLOSED/UP position.





#### (2x) DOUBLE FOLD

- Once the board is completely dry and fully deflated, lay it deck-side up on a flat surface.
- Fold the entire board in half lengthwise, then 2 begin folding in sections, starting from the nose.
- Continue folding until the board is completely rolled up, then set the air valve to the CLOSED/UP position.



## Tips on how to properly store your ULTRA™ inflatable paddle board.

Rinse and Clean: After each use, especially in salt water, rinse your ULTRA™ board thoroughly, including the PVC, handles, and deck. Apply a little bit of soap to help remove any dirt or residue, and then rinse again to ensure it is clean.

Dry Completely: Before storing your ULTRA™ board, ensure it is completely dry. Pay special attention to the deck padding and woven fibers, as any moisture left in these areas could lead to mold growth or compromise the glue holding the PVC together.

Roll and Store: Once your ULTRA™ board is fully dry, roll it up and store it in a temperature-controlled environment. Avoid extreme heat and humidity, as they can also promote mold growth and potentially compromise the PVC's glue.

Deflate Slightly: If you plan on using your ULTRA™ board throughout the day or over the weekend, it's advisable to deflate it by 1-2 PSI when not in use. This precaution prevents overinflation caused by heat or direct sunlight, which can lead to seam compromise. Deflating your ULTRA™ board slightly will help it handle environmental changes more effectively.

If either bungee storage area shows signs of wear and tear, it is possible to remove and replace them with new bungees.

For glue issues on your board that are under  $\frac{1}{2}$  inch in size, we recommend fixing the problem by using PVC glue to secure the affected section. However, if the glue issue is larger than  $\frac{1}{2}$  inch, we advise reaching out to our Customer Experience team for further evaluation and assistance. They will be able to provide appropriate guidance.

By following these steps, you can ensure that your ULTRA™ board remains in good condition and ready for your next





Have questions? We're here to help.

1-866-985-8367

irockersup.com