

2005-10 Mustang GT Fuel Rail Adapter

PART NUMBER 00-01805

INSTALLATION INSTRUCTIONS

This Nitrous Outlet Vehicle Specific Billet Fuel Rail Adapter is designed specifically for the 2005-2010 Ford Mustang GT with a 4.6/5.4 3 valve engine. If you need any assistance during installation or if you have questions about this plate system, call our Tech Help Line at (254) 848-4300.

Tools Needed for Installation*:

- 8mm Deep Socket
- 13mm Deep Socket
- Ratchet
- 9/16" Wrench
- 4mm Allen Wrench

*These are the tools required for installation of this kit on a stock vehicle. If your vehicle has aftermarket parts, other tools may be required.



Step 1:

Locate the fuel disconnect on the driver's side of the intake manifold.



Step 2:

Disconnect the plug from the fuel pressure sensor.



Step 3:

Use an 8mm deep socket to remove the both fuel pressure sensor mounting bolts.

IMPORTANT- ALL APPROPRIATE SAFETY EQUIPMENT (GLOVES, TOOLS ETC.) MUST BE USED DURING THE INSTALLATION OF THIS PRODUCT(S). NITRO DAVE'S LLC ACCEPTS NO RESPONSIBILITY FOR INJURIES RESULTING IN THE INSTALLATION OF ANY PRODUCT(S). NITROUS OXIDE IS FOR OFF-ROAD USE ONLY.



2005-10 Mustang GT Fuel Rail Adapter

PART NUMBER 00-01805

INSTALLATION INSTRUCTIONS



Step 4:

Place the adapter block between the fuel pressure sensor and the fuel rail with the fuel fitting pointed toward the rear of the vehicle. Use the supplied hardware and 4mm Allen wrench to bolt the adapter and sensor to the fuel rail.



Step 5:

Install the U-shaped hardline between the adapter block and the fuel solenoid. 7/16" wrench.



Step 6:

Reconnect the plug to the fuel pressure sensor.



IMPORTANT- ALL APPROPRIATE SAFETY EQUIPMENT (GLOVES, TOOLS ETC.) MUST BE USED DURING THE INSTALLATION OF THIS PRODUCT(S). NITRO DAVE'S LLC ACCEPTS NO RESPONSIBILITY FOR INJURIES RESULTING IN THE INSTALLATION OF ANY PRODUCT(S). NITROUS OXIDE IS FOR OFF-ROAD USE ONLY.