

Installation Instructions for Foot Pegs for 2007-2018 Jeep® JK, 4 Door



Thank you for purchasing your new Skid Row Offroad Foot Pegs.

Your Foot Peg package should come complete with the following parts:

- 1. (1) Driver's Side Front Foot Peg (shown on left, bottom)
- 2. (1) Passenger Side Front Foot Peg (shown on right, bottom)
- 3. (1) Driver's Side Rear Foot Peg (shown on left, top)
- 4. (1) Passenger Side Rear Foot Peg (shown on right, top)
- 5. (4) Hairpin Cotter Pins
- 6. (2) Vinyl Caps
- 7. (2) Rubber Bumpers

Step 1: Using a little liquid soap, push the rubber bumper into the hole on each rear foot peg. It's helpful to twist the bumper a little to get it into the hole.

Step 2: Slip the vinyl caps onto the tabs of the front foot pegs.

Step 3: After removing your Jeep's doors, place each foot peg into the lower hinge on each side, put one of the hairpin cotter pins through the hole below the hinge, and you're ready to enjoy driving doorless with a comfortable place to put your foot!

We hope you enjoy your new Foot Pegs! Sincerely, Your friends at Skid Row Offroad



Skid Row Offroad 100 Creek Road, Carlisle, PA 17013 Phone 717-701-8315



www.SkidRowOffroad.com