

# EWCO

ELECTROLYZED WATER CO.

## OPERATION MANUAL

EWCO 240 System



EWCO  
+1 754-800-4020  
[service@ewco.com](mailto:service@ewco.com)

# Table of Contents

Specifications	Page 3
Requirements	Page 3
Buttons and Display	Page 4
Operational Modes	Page 4
Settings & Performance	Page 5
System Alarms	Page 5
Safety Precautions	Page 6
Additive Formulas	Page 6
Changing Additive	Page 7
Controlling Concentration	Page 7
Measuring Concentration	Page 9
Routine Maintenance	Page 9

## Specifications

<b>Model</b>	EWCO 240
<b>Power</b>	AC 110/220V 50/60HZ 180W
<b>Dimensions</b>	32 x 17 x 42 cm (12.5 x 6.5 x 16.5 in)
<b>Weight</b>	11.8 kg (26 lbs.)
<b>Production Cell Type</b>	Single cell electrolysis for generating hypochlorous acid (HOCl)
<b>Concentration Range</b>	20 to 150 ppm of free available chlorine (FAC)
<b>Ampere Settings</b>	13 to 22 amp
<b>Pump Speed Settings</b>	0 to 19 (max. speed to min. speed)

## Requirements



<b>Ambient Temperature</b>	5 to 50 °C (41 to 122 °F)
<b>Feed Water &amp; Brine Temperature</b>	10 to 30 °C (50 to 86 °F)
<b>Feed Water &amp; Brine Water Quality</b>	Hardness < 80 ppm (higher will damage the electrolysis cells)
<b>Humidity</b>	Less than 96% Relative Humidity (RH)
<b>Minimum Flow Rate</b>	3 L/min
<b>Maximum Water Pressure</b>	40 PSI

## Buttons and Display




No	Description
1	LED display
2	System is running
3	Check error code in LED display
4	System RUN On/Off
5	Mode button (see uses below)
6	Set button (see uses below)
7	Reset alarm to resume running

## Operational Modes

<p><b>Standard Mode</b></p> 	<p>The standard mode is the default and should be used unless connecting system to a holding tank with a float sensor.</p> <p>Setting to standard mode:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release</li> <li>2. Press “Reset” button once</li> <li>3. Press and hold “Mode” button for 3 seconds and release</li> </ol>
<p><b>Level Mode</b></p> 	<p>This mode must be used when connecting the system to a holding tank using a float sensor. The system will automatically stop running when the water level rises to the level to activate the float sensor.</p> <p>Setting to level mode:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release</li> <li>2. Press “Set” button once</li> <li>3. Press and hold “Mode” button for 3 seconds and release</li> </ol>

## Settings & Performance

<p>Flow Rate measured in Liters per minute (L)</p> 	<p>The flow rate can be controlled by tightening or loosening the inflow water valve. A higher flow rate will decrease the concentration of free available chlorine (FAC) and a lower flow rate will increase the concentration of FAC.</p> <p>Displaying the flow rate:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release. LED display will begin to blink.</li> <li>2. Press “Mode” button until liters per minute (L) setting is displayed.</li> </ol>
<p>Voltage (v)</p>	<p>The voltage is a performance measurement and is not adjustable.</p> <p>Displaying the voltage:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release. LED display will begin to blink.</li> <li>2. Press “Mode” button until voltage (v) setting is displayed.</li> </ol>
<p>Ampere (A) Max. ampere: 22 Min. ampere: 13</p>	<p>The ampere is an adjustable setting. The range is from 13 to 22 ampere. Higher settings will increase the concentration of free available chlorine (FAC).</p> <p>Adjusting the ampere:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release. LED display will begin to blink.</li> <li>2. Press “Mode” button until ampere (A) setting is displayed.</li> <li>3. Press “Set” button to increase the ampere. Press “Reset” button to decrease the ampere.</li> <li>4. Press and hold “Mode” button for 3 seconds and release to complete.</li> </ol>
<p>Pump Speed (PS) Max. speed: 0 Min. speed: 19</p>	<p>The pump speed is an adjustable setting. The range is from 0 to 19. Lower settings will increase the pump speed and thus increase the additive dosed into the electrolysis cell. For most purposes, the pump speed should be kept in mid-range.</p> <p>Adjusting the pump speed:</p> <ol style="list-style-type: none"> <li>1. Press and hold “Set” button for 3 seconds and release. LED display will begin to blink.</li> <li>2. Press “Mode” button until pump speed (PS) setting is displayed.</li> <li>3. Press “Set” button to increase the pump speed. Press “Reset” button to decrease the pump speed.</li> <li>4. Press and hold “Mode” button for 3 seconds and release to complete.</li> </ol>

## System Alarms

Error Code	Reason	Action
<b>Err1</b>	Low Flow	Check the flow of the feed water into the equipment. Once corrective action has been taken to sustain the water flow above 3 L/min, press the “Reset” button to cancel the alarm. If unresolved, contact the service center.
<b>Err2</b>	Low Current	Disconnect additive tank and refill with a new brine. Re-attach the tank once completely dissolved. Press the “Reset” button to cancel the alarm. If unresolved, contact the service center.
<b>Err3</b>	High Current	Disconnect additive tank and refill with a new brine. Re-attach the tank once completely dissolved. Press the “Reset” button to cancel the alarm. If unresolved, contact the service center.
<b>Err4</b>	Low Voltage	The voltage is abnormally low. Please contact the service center for further assistance.
<b>Err5</b>	Fan Error	The cooling fan is not functioning. Please contact the service center for further assistance.

Safety Precautions	Brine / Additive Formulas
Ventilation Risks	Electrolyzed water contains small quantities of hydrogen gas (H <sub>2</sub> ), chlorine dioxide gas (ClO <sub>2</sub> ), and ozone gas (O <sub>3</sub> ) that is released from solution into the air. These gases, if accumulated, can be explosive. Electrolyzed water contains free chlorine molecules. Free chlorine molecules have the potential to form chlorine gas (Cl <sub>2</sub> ) when the pH of the solution becomes acidic. Chlorine gas, if inhaled, can cause respiratory irritation or injury and is a health risk. Equipment must be installed in a ventilated area to avoid the accumulation of gases. Do not install equipment near heat sources over 400°C (750°F)
Electric Shock and Fire Risks	Only use certified outlets. Do not place the equipment in water or allow the equipment to be exposed to external sources of water. Do not operate equipment if electric cord is damaged. Do not operate equipment in environments of relative humidity greater than 95%. In the event of an electric shock or fire, equipment must be removed from the power source immediately.

Formula #	HOCl Solution	Formula Instructions
<b>1</b>	Using Formula #1 the system will generate a free chlorine solution in which over 25% of the chlorine molecules will be hypochlorous acid (HOCl).  pH ≈ 7-8 **GOOD**	<p>Formulation</p> <ul style="list-style-type: none"> <li>• 28% Food Grade Salt (NaCl).</li> <li>• 72% Water (tap water, reverse osmosis or distilled)</li> </ul> <p>When preparing 2-Liter additive tank:</p> <ol style="list-style-type: none"> <li>1. Add 550 g (≈2 cups) of salt*</li> <li>2. Fill remainder with water (1400 mL)</li> <li>3. Shake until salt fully dissolved</li> </ol> <p>* No iodine or other additives (ie. kosher salt)</p>
<b>2</b>	Using Formula #2 the system will generate a free chlorine solution in which over 70% of the chlorine molecules will be hypochlorous acid (HOCl).  pH ≈ 6-7 **BETTER**	<p>Formulation</p> <ul style="list-style-type: none"> <li>• 28% Food Grade Salt (NaCl).</li> <li>• 72% Food Grade 5% White Distilled Vinegar</li> </ul> <p>When preparing 2-Liter additive tank:</p> <ol style="list-style-type: none"> <li>1. Add 550 g (≈2 cups) of salt*</li> <li>2. Fill remainder with 5% distilled vinegar (1400 mL)</li> <li>3. Shake until salt fully dissolved</li> </ol> <p>* No iodine or other additives (ie. kosher salt)</p>
<b>3</b>	Using Formula #3 the system will generate a free chlorine solution in which over 90% of the chlorine molecules will be hypochlorous acid (HOCl).  pH ≈ 5-6 **BEST**	<p><b>ATTENTION:</b> Proper personal protective gear required when preparing additive with hydrochloric acid (HCl).</p> <p>Formulation</p> <ul style="list-style-type: none"> <li>• 72% Water (tap water, reverse osmosis or distilled)</li> <li>• 19% food grade salt (NaCl).</li> <li>• 9% hydrochloric acid (HCl).</li> </ul> <p>When preparing 2-Liter additive tank:</p> <ol style="list-style-type: none"> <li>1. Add 380 g of salt*</li> <li>2. Add 1440 mL of water</li> <li>3. Shake until salt fully dissolved</li> <li>4. Add 180 mL of hydrochloric acid (HCl)**</li> </ol> <p>* No iodine or other additives (ie. kosher salt) **Use technical grade HCl (32%) for general sanitation. For food contact, must use FCC grade HCl (35-37%).</p>



## Changing Additive

Replenish additive tank when low. If additive runs out, the system will stop and display Error 2.

### Changing Additive Using Formula #1

- Power Off system
- Remove suction line and cap from additive tank
- Add 2 cups of salt to additive tank
- Fill remainder of additive tank with tap water
- Replace cap and shake until dissolved
- Replace suction line
- Power On system and press “Reset” button

## Controlling Concentration

The following settings are recommendations for reaching approximate concentrations of free available chlorine (FAC) in solution measured in parts per million (ppm). The 3 variables below can be adjusted to change the concentration.

1. Flow Rate (L/min) – controlled by blue valve allowing feed water to flow into system
2. Ampere (A) - controlled by system settings
3. Pump Speed (PS) - controlled by system settings

### Using Additive Formula 1 (Water and Food Grade Salt)

Flow Rate 3.0 L/min

	17.5 A	22.0 A
0 PS	85 ppm	100 ppm
2 PS	82 ppm	96 ppm
4 PS	79 ppm	92 ppm
6 PS	76 ppm	88 ppm
8 PS	73 ppm	86 ppm
10 PS	70 ppm	82 ppm

### Using Additive Formula 1 (Water and Food Grade Salt)

Flow Rate 4.0 L/min

	17.5 A	22.0 A
0 PS	64 ppm	80 ppm
2 PS	62 ppm	77 ppm
4 PS	60 ppm	74 ppm
6 PS	58 ppm	71 ppm
8 PS	56 ppm	68 ppm
10 PS	54 ppm	65 ppm

## Using Additive Formula 1 (Water and Food Grade Salt)

Flow Rate 5.0 L/min

	17.5 A	22.0 A
0 PS	60 ppm	75 ppm
2 PS	57 ppm	71 ppm
4 PS	54 ppm	67 ppm
6 PS	51 ppm	63 ppm
8 PS	48 ppm	59 ppm
10 PS	45 ppm	55 ppm

## Using Additive Formula 2 (Distilled White Vinegar and Food Grade Salt)

Flow Rate 3.0 L/min

	17.5 A	22.0 A
0 PS	75 ppm	90 ppm
2 PS	72 ppm	86 ppm
4 PS	69 ppm	82 ppm
6 PS	66 ppm	78 ppm
8 PS	63 ppm	76 ppm
10 PS	60 ppm	72 ppm

## Using Additive Formula 2 (Distilled White Vinegar and Food Grade Salt)

Flow Rate 4.0 L/min

	17.5 A	22.0 A
0 PS	54 ppm	70 ppm
2 PS	52 ppm	67 ppm
4 PS	50 ppm	64 ppm
6 PS	48 ppm	61 ppm
8 PS	46 ppm	58 ppm
10 PS	44 ppm	55 ppm

## Using Additive Formula 2 (Distilled White Vinegar and Food Grade Salt)

Flow Rate 5.0 L/min

	17.5 A	22.0 A
0 PS	50 ppm	65 ppm
2 PS	47 ppm	61 ppm
4 PS	44 ppm	57 ppm
6 PS	41 ppm	53 ppm
8 PS	38 ppm	49 ppm
10 PS	35 ppm	45 ppm



### Using Additive Formula 3 (Water, Food Grade Salt, and HCl)

Flow Rate 3.0 L/min

	17.5 A	22.0 A
0 PS	115 ppm	150 ppm
2 PS	110 ppm	144 ppm
4 PS	105 ppm	138 ppm
6 PS	100 ppm	132 ppm
8 PS	95 ppm	126 ppm
10 PS	90 ppm	120 ppm

### Using Additive Formula 3 (Water, Food Grade Salt, and HCl)

Flow Rate 4.0 L/min

	17.5 A	22.0 A
0 PS	74 ppm	95 ppm
2 PS	70 ppm	90 ppm
4 PS	66 ppm	85 ppm
6 PS	62 ppm	80 ppm
8 PS	58 ppm	75 ppm
10 PS	54 ppm	70 ppm

### Using Additive Formula 3 (Water, Food Grade Salt, and HCl)

Flow Rate 5.0 L/min

	17.5 A	22.0 A
0 PS	66 ppm	85 ppm
2 PS	62 ppm	80 ppm
4 PS	58 ppm	75 ppm
6 PS	54 ppm	70 ppm
8 PS	50 ppm	65 ppm
10 PS	46 ppm	60 ppm

## Measuring Concentration

The concentration of free available chlorine (FAC) can be measured with standard chlorine test paper. The range and sensitivity measurable are 10, 50, 100, and 200 ppm.

For greater accuracy or to measure high range free available chlorine levels, the chlorine concentration can be measured with a high range chlorine photometer.

Supplies for measuring free chlorine concentration can be found at: [Store.EWCO.com](http://Store.EWCO.com) and search SKU listed below.

Chlorine Test Paper (SKU: P-1050)

Chlorine Photometer (SKU: P-1047)

## Maintenance

Over time and depending on use, mineral scale can build-up on the electrolysis cells. Mineral scale build-up depends on the quality of the inflow water. If the hardness of the inflow water is less than 80 ppm, scale will build up very slowly and the system may not require maintenance for many years. Using the incorrect salt can cause mineral scale to build up very quickly. If mineral scale does build up, the electrical current required to generate a free chlorine solution of hypochlorous acid will be disrupted.

### When to do Maintenance:

When the actual ampere of the system drops to a level below 90% of the set ampere, the systems electrolysis cells should be descaled of mineral deposits.

### How to do Maintenance:

Simply run the system using additive formula #3 with hydrochloric acid (HCl). The HCl will descale the mineral deposits from the electrolysis cells. Run the system until the actual ampere returns to the set ampere. This could take 30 minutes or several hours depending on the amount of scale.