Acetone

SECTION I - IDENTIFICATION

Solvent Direct, Inc



 DATE PREPARED:
 9/9/1996

 REVISION DATE:
 10/14/2020

 CHEMTEL:
 800-255-3924

 PRODUCT CODE:
 ACE

WWW.SOLVENTDIRECT.COM

ADDRESS: 2711 N Sepulveda Blvd.,

#237 Manhattan Beach, CA 90266

EMERGENCY PHONE NUMBER: 1-833-PURE-GAS

PRODUCT NAME: Acetone

CHEMICAL FAMILY:

CAS NUMBER: 67-64-1

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Flammable Liquids

Acute Toxicity, Oral

Skin Corrosion/Irritation

Category 3

Serious Eye Damage/Eye Irritation

Category 2A

DANGER!

GHS LABEL:





Hazard Statements

H225 Highly flammable gas and vapor

H302 Harmful if swallowed

H316 Causes mild skin irritation
H319 Causes serious eye irritation

Acetone

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P330	Rinse mouth.
P332+313	If skin irritation occurs: get medical advice/attention.
P337+313	If eye irritation persists get medical advice/attention.
P370+378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+235	Store in a well ventilated place. Keep cool.
P501	Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Acetone	67-64-1	100%	750 ppm	500 ppm

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing

immediately and launder before reuse. If irritations persist, seek immediate

medical attention.

Acetone

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

Ingestion: If swallowed do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

Unusual Fire Fighting Hazards: Product is flammable and may be ignited by heat, sparks, flames or other

sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard

indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or

release.

Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

Methods for Cleaning Up: Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
- "Empty" containers retain residue and/or vapor and may be dangerous.
 Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

Acetone

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS#	OSHA PEL	ACGIH TLV
Acetone	67-64-1	750 ppm	500 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Monitoring: Follow accepted work practices for handling a flammable material.

Do not eat, drink or smoke in areas where this chemical is used or stored.

Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

Skin Protection: Impervious solvent resistant gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is unknown

or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	Clear, Colorless Liquid		
Odor	Strong Ketone Odor		
pH@25°C	-		
Melting/Freezing Point	-		
Boiling Point	56°C (133°F)		
Flashpoint	-0.4°F (-18°C); TCC		
Specific Gravity	0.79		
Solubility	Complete		
Auto-Ignition Temperature	-		
Decomposition Temperature	-		
VOC Content	0%		
Odor Threshold	-		
Boiling Range	133°F		
Evaporation Point	11.6(Butyl Acetate=1)		
Flammable Limits - Upper	12.8%		
Flammable Limits - Lower	2.5%		
Vapor Pressure	184 mmHg @ 20°C		
Vapor Density (Air=1)	2 (Air=1)		
Viscosity	-		

SECTION X - STABILITY AND REACTIVITY

Acetone

Stability: Stable

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO, CO2, and various hydrocarbons under combustion

conditions.

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: Low to moderate degree of toxicity by inhalation.

May cause respiratory tract irritation. Inhalation of vapors may cause

drowsiness and dizziness.

Eye Contact: Causes eye irritation including stinging, watering and redness which

may result in corneal injury.

Prolonged contact can result in chemical burns and permanent tissue

damage.

High vapor concentrations are irritating to the eyes.

Skin Contact: Contact may cause mild skin irritation including redness, burning and

drying/cracking of the skin.

No harmful effects from skin adsorption are expected.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

May produce CNS depression and kidney damage which may be fatal.

Toxicity:

Component Name	LD50	LC50
Acetone	Oral - mouse - 3,000 mg/kg	Inhalation - mouse - 4H/44,000 mg/m3

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Acetone

Mobility: Information not available.

Degradability: Information not available.

Bioaccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers, or water courses. Empty containers should be air dried before disposing.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Acetone

Contains:

Hazard Class and Label: 3

Identification Number: UN 1090

Packaging Group:

Label Required:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	N/A	X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS#	% by wt.	RQ (lbs.)
Acetone	67-64-1	100%	5,000

California Prop. 65 - This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

Acetone

SECTION XVI - OTHER INFORMATION

HMIS Health:	2
HMIS Flammability	3
HMIS Reactivity	0

Specification Information

Department issuing data sheet: Compliance

Email address: compliance@transcheminc.com

Training necessary: Follow all local, state and federal regulations

Intended Use of Product:

Seller and manufacturer disclaim any implied or expressed warranties, including warranties of merchantability or fitness of this product for any particular purpose. In no event shall seller be liable for any claim for incidental or consequential damages arising out of or in connection with the sale, delivery, transportation or use of this product. Seller's and manufacturer's liability in all events is limited to, and shall not exceed the purchase price paid for this product.

^{*}Chronic health hazard - Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.