

**Safety Data Sheet**  
Methanol

**SECTION I - IDENTIFICATION**

Solvent Direct, Inc



WWW.SOLVENTDIRECT.COM

DATE PREPARED: ..... 7/11/2002  
REVISION DATE: ..... 7/6/2021  
CHEMTEL: ..... 800-255-3924  
PRODUCT CODE: ..... Methanol

ADDRESS: ..... 2711 N Sepulveda Blvd.,  
#237 Manhattan Beach, CA 90266

EMERGENCY PHONE NUMBER: ..... 1-833-PURE-GAS

PRODUCT NAME: .....  
CHEMICAL FAMILY: ..... Methanol

CAS NUMBER: .....  
67-56-1

**SECTION II - HAZARDOUS IDENTIFICATION**

**GHS CLASSIFICATION:**

**Classification**

Flammable Liquids	Category 2
Acute Toxicity, Oral	Category 3
Acute Toxicity, Dermal	Category 3
Acute Toxicity, Inhalation	Category 3
Specific target organ toxicity, single exposure	Category 1

**DANGER!**

**GHS LABEL:**



**Hazard Statements**

H225	Highly flammable gas and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

# Safety Data Sheet

## Methanol

### Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated are.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P307+311	IF exposed: Call a POISON CENTER or doctor/physician.
P311	Call a POISON CENTER or a doctor/physician.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P322	Specific measures (see ... on this label).
P361	Remove/Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P370+378	In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

# Safety Data Sheet

## Methanol

### SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Methanol	67-56-1	100%	200 ppm(Skin)	200 ppm(Skin)

### SECTION IV - FIRST AID MEASURES

**Contact with eyes:** Flush with water for 15 minutes. Seek immediate medical attention.

**Skin contact:** Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

**Inhalation:** Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

**Ingestion:** Give large quantities of water . Never give anything by mouth to an unconscious person.

### SECTION V - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

**Unusual Fire Fighting Hazards:** Product is flammable and may be ignited by heat, sparks, flames or other sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

# Safety Data Sheet

## Methanol

### SECTION VI - ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or release.  
Evacuate all unprotected personnel from the area.

**Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.  
Notify proper authorities. Reportable Quantity is 5,000 pounds or 758 gallons.  
Contain spill if it can be done with minimal risk.

**Methods for Cleaning Up:** Use foam on spills to minimize vapors.  
Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

### SECTION VII - HANDLING AND STORAGE

**Handling and Storage:**

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
- "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Methanol	67-56-1	200 ppm(Skin)	200 ppm(Skin)

**Engineering Controls:** Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

**Monitoring:** Follow accepted work practices for handling a flammable material.  
Do not eat, drink or smoke in areas where this chemical is used or stored.  
Have eye wash stations and safety showers readily available.

#### Personal Protective Equipment (PPE)

**Eye Protection:** Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

**Skin Protection:** Impervious solvent resistant gloves.  
Impervious apron and work boots recommend where splashing may occur.

**Respiratory Protection:** Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

**Safety Data Sheet**  
Methanol

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Clear, Colorless Liquid
<b>Odor</b>	Strong Characteristic Alcohol Odor
<b>pH@25°C</b>	-
<b>Melting/Freezing Point</b>	-
<b>Boiling Point</b>	64.6°C (148°F)
<b>Flashpoint</b>	54°F (11°C); TCC
<b>Specific Gravity</b>	0.7793
<b>Solubility</b>	Complete
<b>Auto-Ignition Temperature</b>	-
<b>Decomposition Temperature</b>	-
<b>VOC Content</b>	100% (6.61#/gal)
<b>Odor Threshold</b>	-
<b>Boiling Range</b>	148°F
<b>Evaporation Point</b>	2.0 (Butyl Acetate=1)
<b>Flammable Limits - Upper</b>	36.5%
<b>Flammable Limits - Lower</b>	5.5%
<b>Vapor Pressure</b>	96 mmHg @ 20°C
<b>Vapor Density (Air=1)</b>	1.11 (Air=1)
<b>Viscosity</b>	-

**SECTION X - STABILITY AND REACTIVITY**

**Stability:** Stable

**Conditions to Avoid:** Extreme heat and ignition sources.

**Hazardous Decomposition/Byproducts:** CO, CO<sub>2</sub>, and noxious smoke under extreme fire conditions

**Hazardous Polymerization:** Will not occur.

**Polymerization Conditions to Avoid:** None

**Safety Data Sheet**  
Methanol

**SECTION XI - TOXICOLOGICAL INFORMATION**

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** Low to moderate degree of toxicity by inhalation.  
May cause respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

**Eye Contact:** Causes eye irritation including stinging, watering and redness which may result in corneal injury.

**Skin Contact:** Contact may cause mild skin irritation including redness, burning and drying/cracking of the skin.  
Repeated or prolonged contact with large amounts of this material may result in absorption through the skin to produce toxic effects.

**Ingestion:** Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.  
Moderate to high degree of toxicity by ingestion. May be harmful or fatal if swallowed.

**Toxicity:**

Component Name	LD50	LC50
Methanol	Oral - Human - 143 mg/kg; Oral - rat - 1,187 - 2,769 mg/kg;	Inhalation - rat - 4 h - 128.2 mg/l; Inhalation - rat - 6 h - 87.6

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

**SECTION XII - ECOLOGICAL INFORMATION**

**Ecotoxicity:** Information not available.

**Mobility:** Information not available.

**Degradability:** Information not available.

**BioAccumulation:** Information not available.

**Safety Data Sheet**  
Methanol

**SECTION XIII - WASTE DISPOSAL CONSIDERATIONS**

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers, or water courses. Empty containers should be air dried before disposing.

**SECTION XIV - TRANSPORT INFORMATION**

**DOT SHIPPING INFORMATION**

**Proper Shipping Name:** Methanol

**Contains:**

**Hazard Class and Label:** 3

**Identification Number:** UN 1230

**Packaging Group:** II

**Label Required:**

**SECTION XV - REGULATORY INFORMATION**

**TSCA STATUS:**..... The components of this product are listed on the TSCA Inventory

**SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:**

No chemicals in this material are subject to the reporting requirements.

**SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:**

Acute	Chronic	Fire	Pressure	Reactive
X	X	X		

**SARA TITLE III SECTION 313 SUPPLIER INFORMATION:**

Component Name	CAS #	% by wt.
Methanol	67-56-1	100%

**CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:**

Component Name	CAS #	% by wt.	RQ (lbs.)
Methanol	67-56-1	100%	5,000

**Clean Air Act:**

CAS# 67-56-1 is listed as a hazardous air pollutant (HAP).  
This material does not contain any Class 1 Ozone depletors.  
This material does not contain any Class 2 Ozone depletors

**California Prop. 65 Components WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Methanol CAS-No.67-56-1

**Safety Data Sheet**  
Methanol

**SECTION XVI - OTHER INFORMATION**

**HMIS Health:** .....2  
**HMIS Flammability:**.....3  
**HMIS Reactivity** .....0

**Additional:**

**Specification Information**

**Department issuing data sheet:** Compliance

**Email address:** compliance@transcheminc.com

**Training necessary:** Follow all local, state and federal regulations

**Intended Use of Product:**

Seller and manufacturer disclaim any implied or expressed warranties, including warranties of merchantability or fitness of this product for any particular purpose. In no event shall seller be liable for any claim for incidental or consequential damages arising out of or in connection with the sale, delivery, transportation or use of this product. Seller's and manufacturer's liability in all events is limited to, and shall not exceed the purchase price paid for this product.