SOLVENT DIRECT

 Date
 : 06/15/2013

 Version
 : 2

Safety Data Sheet

PH DOWN LIQUID

1. Product and company identification			
Product name	: PH DOWN LIQUID		
Material uses	: Not available.		
Supplier/Manufacturer	Solvent Direct Inc. 19129 S Hamilton Ave Gardena, CA 90248		
MSDS authored by <u>In</u>	: KMK Regulatory Services Inc.		
case of emergency	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887 (collect calls accepted)		

2. Hazards identification

Emergency overview	
Physical state	: Liquid.
Color	: Yellow.
Odor	: Odorless.
Signal word	: DANGER!
Hazard statements	: CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY BE HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.
Precautionary measures	: Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not get in eyes. Do not get on skin. Do not eat, drink or smoke when using this product. Keep container tightly closed. Wash thoroughly after handling.
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of entry	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effect	<u>is</u>
Inhalation	: Corrosive to the respiratory system. Exposure to decomposition products may cause a
	health hazard. Serious effects may be delayed following exposure.
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.
Skin	: Corrosive to the skin. Causes burns.
Eyes	: Corrosive to eyes. Causes burns.
Potential chronic health effe	ects
Chronic effects	: Contains material that may cause target organ damage, based on animal data.
Carcinogenicity	: No known significant effects or critical
Mutagenicity	hazards.: No known significant effects or critical
Teratogenicity	hazards.: No known significant effects or critical
Developmental effects	hazards. : No known significant effects or critical
Fertility effects	hazards. : No known significant effects or critical
	hazards.

2. Hazards identification

: Contains material which may cause damage to the following organs: upper respiratory tract, skin, eye, lens or cornea.

Over-exposure signs/symptoms

Target organs

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eyes	: Adverse symptoms may include the following: pain watering redness
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
Ammonium dihydrogenorthophosphate	7664-38-2 7722-76-1 77-92-9	10 - 30 5 - 10 5 - 10

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.		
Skin contact	 In case of contact, immediately flush skin with plenty of water for at least 20 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately. 		
Inhalation	 Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. 		
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		

5. Fire-fighting measures

Flammability of the product	: No specific fire or explosion hazard.
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: No special precaution is required.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.

7. Handling and storage

```
Storage
```

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Separate from alkalis. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient		Exposure limits		
Phosphoric acid		ACGIH TLV (United States, 3/2012). STEL: 3 mg/m ³ 15 minutes. TWA: 1 mg/m ³ 8 hours. NIOSH REL (United States, 6/2009). STEL: 3 mg/m ³ 15 minutes. TWA: 1 mg/m ³ 10 hours. OSHA PEL (United States, 6/2010). TWA: 1 mg/m ³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1 mg/m ³ 8 hours. STEL: 3 mg/m ³ 15 minutes.		
Ammonium dihydrogenorthophosphat	te	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Form: Dust		
Recommended monitoring procedures	atmosphere c the ventilation protective equ Reference to	contains ingredients with exposure limits, personal, workplace or biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory uipment. Reference should be made to appropriate monitoring standards. national guidance documents for methods for the determination of bstances will also be required.		
Engineering measures	or mist, use p	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.		
Hygiene measures	eating, smoki Appropriate te Wash contam	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Personal protection				
Respiratory	standard if a i based on kno	y fitted, air-purifying or supplied air respirator complying with an approved risk assessment indicates this is necessary. Respirator selection must be wn or anticipated exposure levels, the hazards of the product and the safe of the selected respirator.		
Hands	worn at all tim necessary. C during use tha noted that the glove manufa	istant, impervious gloves complying with an approved standard should be the when handling chemical products if a risk assessment indicates this is considering the parameters specified by the glove manufacturer, check at the gloves are still retaining their protective properties. It should be time to breakthrough for any glove material may be different for different cturers. In the case of mixtures, consisting of several substances, the e of the gloves cannot be accurately estimated.		
Eyes	assessment i dusts. If cont assessment i	ar complying with an approved standard should be used when a risk ndicates this is necessary to avoid exposure to liquid splashes, mists or act is possible, the following protection should be worn, unless the ndicates a higher degree of protection: chemical splash goggles and/or f inhalation hazards exist, a full-face respirator may be required instead.		

8. Exposure controls/personal protection

Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid.
Color	: Yellow.
Odor	: Odorless.
рН	: 1.2
Boiling/condensation point	: 104°C (219.2°F)
Melting/freezing point	: -8°C (17.6°F)
Relative density	: 1.13
Vapor pressure	: 2.3 kPa (17.5 mm Hg) [room temperature]
Viscosity	: Kinematic (room temperature): 0.01 cm ² /s (1 cSt)
Solubility	: Easily soluble in the following materials: cold water and hot water.
Partition coefficient (LogKow)	: There is no data available.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials, metals, acids and alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phosphoric acid Ammonium	LD50 Oral LD50 Dermal	Rat Rabbit	1.25 g/kg >5000 mg/kg	-
dihydrogenorthophosphate			0 0	-
	LD50 Oral	Rat	>2000 mg/kg	-
Citric acid	LD50 Oral	Rat	3 g/kg	-

Chronic toxicity

There is no data available.

Irritation/Corrosion

PH DOWN LIQUID

11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Citric acid	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
	Skin - Mild irritant	Rabbit	-	Micrograms 24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	0.5 Mililiters	-

<u>Sensitizer</u>

Skin	: There is no data available.
Respiratory	: There is no data available.
Carcinogenicity	
There is no data available.	
Mutagenicity	
There is no data available.	
Teratogenicity	
There is no data available.	
Reproductive toxicity	
There is no data available.	

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Citric acid	Acute LC50 160000 μg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours

Persistence/degradability

There is no data available.

13. Disposal considerations

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

PH DOWN LIQUID

14. Transport information						
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1805	PHOSPHORIC ACID, SOLUTION RQ(Phosphoric Acid)	8	111	Conserver 3	Reportable quantity 24449.9 lbs / 11100.2 kg [2595 gal / 9823.2 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
IMDG Class	UN1805	PHOSPHORIC ACID, SOLUTION	8			-
IATA-DGR Class	UN1805	PHOSPHORIC ACID, SOLUTION	8	111	ALL REAL	-
PG* : Packing group	-1	Exemption to the above	e classificatio	on may ap	ply.	AERG : 153

15. Regulatory information

HCS Classification	1	Corrosive material Target organ effects
U.S. Federal regulations	:	TSCA 8(a) CDR Exempt/Partial exemption: Not determined
		United States inventory (TSCA 8b): All components are listed or exempted.
		Clean Water Act (CWA) 311: Phosphoric acid
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed
SARA 302/304		
Composition/information of	n	ingredients
No products were found.		
SARA 304 RQ	:	Not applicable.
<u>SARA 311/312</u>		
Classification	:	Reactive Immediate (acute) health hazard
Composition/information of	n	ingredients

PH DOWN LIQUID

15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Phosphoric acid	10 - 30	No.		No.	Yes.	No.
Citric acid	5 - 10	No.		No.	Yes.	No.

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Ammonium dihydrogenorthophosphate	7722-76-1	5 - 10
Supplier notification	Ammonium dihydrogenorthophosphate	7722-76-1	5 - 10

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations	
Massachusetts	: The following components are listed: Phosphoric acid
New York	: The following components are listed: Phosphoric acid
New Jersey	: The following components are listed: Phosphoric acid
Pennsylvania	: The following components are listed: Phosphoric acid
<u>California Prop. 65</u>	
No products were found.	

16. Other information

Label requirements	:	SWALLOW	/ED	. C	,	IAL T	ND SKIN BURNS. MAY BE HARMFUL IF HAT MAY CAUSE TARGET ORGAN	
Hazardous Material Information System (U.S.A.)	:	Health :	3	*	Flammability :	0	Physical hazards : 0	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection	: Health :	3	Flammability :	0	Instability :	0
Association (U.S.A.)						

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue mm/dd/yyyy	: 06/15/2013
Date of previous issue	: 03/15/2013
Version	: 2
Revised Section(s)	: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.

16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.