



PRODUCT DATA SHEET

SPR-302

Non-Contact High Voltage Detector



Technical Specifications

Voltage Range	240V, 2kV, 6kV, 11kV, 22kV, 33kV, 132kV, 275kV
Protection Class	IP66
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 60°C
Humidity	85% R.H. @ 40°C
Dimensions	265 mm (H) x 117 mm (W)
Weight	Approx. 590g (including battery)
Power Source	1.5V "C" x 3 Alkaline batteries
Included Accessories	Instruction manual, disconnect hook, fuse extractor head, carry case, batteries
Made In	Taiwan

Features

- Non-contact detection
- Eight voltage settings
- 360° LED indicators
- High-bright LED visual cues
- Sound indication
- Self-test function
- Lightweight and robust design
- Waterproof (IP66)
- Compatible with most hot sticks

General Specifications

The SPR-302 is a non-contact high voltage detector with a waterproof design, specifically engineered for checking the presence of AC high and low voltages. With eight voltage settings, it offers versatility for various applications, ensuring safe and efficient detection.

Ordering Information

SPR-302 :Non-Contact High Voltage Detector

GET IN TOUCH

E-MAIL : info@spartna.com

PHONE : +971547796588

WEB SITE : WWW.SPARTNA.COM

