

DATA SHEET



TOUCH-FREE TAPWARE

FOR COMMERCIAL & PUBLIC BATHROOMS (Wall Mounted)



+ Hygienic

Saves water

Low Maintenance

Auto shut-off after 1 minute

Durable commercial grade construction

AC mains power and/or 4x AA Battery (lasts 6+ months)

🕠 Inlet pressure range 50kpa - 500kpa

Maximum water temperature 80°C





SF1113PC


BRONTE

YEAR ARANA



DATA SHEET












Touch-free Tapware **SF1113PC - Bronte**



WELS Rating





WEES Racing	o star, s.s. per minute
Max Operating	80° C
Water Supply Temperature	Suitable for cold or warm water supply (with thermostatic mixing valve)
Operation	Auto focus infrared sensor
Recommended working pressure	50-500kPa-Note: New Regulation: $500kPa$ maximum static pressure at any outlet within a building. (Ref. AS/NZS 3500.1)
Finish	Polished Chrome (PC), Matt Black (MB), Brushed Nickel (BN), Champagne (CHP), Brushed Gold (BG), Brushed Brass (BB), Satin Brass (SB), Gunmetal (GM)
Power Supply	DC Battery box (4x AA) or 240V mains supply AC adapter (included)
Sensor Detection	≤1 seconds
Valve closing delay	0.5 ~ 2 seconds
Auto Shut-off	After 60 seconds
Sensing Distance	150mm (15cm) - adjustment possible by remote control (sold separately)
Warranty	5 Year replacement (refer to onvanti.com.au/warranty)

way will not be covered by warranty.

Wipe down with a clean, soft dry cloth. If required use a mild/neutral detergent and water.

Do not use cream cleaners or citrus based cleaning products, as they are abrasive. Use of unsuitable cleaning agents may damage the surface. Any damage caused in this

6 Star, 5.5L per minute

SF1113PC BRONTE

Maintenance & Care