VN202 mkII



- Resolution ± 0.1%
- Accuracy ± 1% full scale
- Easy replacement of sensor
- Long life sensor (expected life 48 months in air)
- Water resistant
- 5 year guarantee on instruments (excl. sensors & cables)
- Calibrate and measure in still gas at 1 bar (1 Atm) stable: no drift due to gas flow
- Fast measuring with minimum gas waste
- Suitable for altitude diving
- Supplied in protective carrying and storage case
- Auto switch-off battery saver
- Model available with auto switch-off disabled





15 Station Road • Cross Hills • Keighley • West Yorkshire • BD20 7DT Tel: +44 (0)1535 634900 • Fax: +44 (0)1535 635582 Email: info@vandagraph.co.uk www.vandagraph.co.uk

Specification	
Range	0 - 100% Oxygen
Accuracy	+/- 1% of full scale
Response Time	90% step change < 10sec
Resolution	+/- 0.1 %
Battery Type	2 x MN1500 LR6 1.5V
Battery Life	12 months (typical)
Sensor Type	R-17VAN (Galvanic)
Sensor Life in Air	Expected 36 - 48 months (10 months in 100% O ₂)
Sensor Output	7.0mV - 13.0mV in air
Dimensions	59mm x 142mm x 26mm
Weight	235g including battery and sensor
Storage Temp	0°C - 50°C (10°C - 50°C recommended)
Operating Temp	0° - 40°C
Case	Splash proof
Waterproofing	IP65 NEMA 4
EMC CE	ISO EN 60601-1-2
RoHS	Complies with RoHS

Accessory Parts List	
0110217	R-17VAN Oxygen Sensor
9730215	DIN KIT Restrictor kit
9711002	B-50074 Flow-diverter
9730210	Quick-Ox Gas Sampling Kit

VN202 with Quick-Ox



Part Numbers: Auto switch-off 7910101 Manual switch-off 7910111

VN202 with DINKIT



Part Numbers: Auto switch-off 7910102 Manual switch-off 7910112