



REVERSE OPERATION ON REQUEST

| $\Delta$ Pressure | Tolerance |
|-------------------|-----------|
| 1,2 Bar           | +/- 15%   |
| 1,3 Bar           | +/- 15%   |
| 2 Bar             | +/- 10%   |
| 2,5 Bar           | +/- 10%   |
| 5 Bar             | +/- 10%   |
| 8 Bar             | +/- 10%   |

Other differential pressure values are also available.

For customized version (type of cable, thread) please contact Euroswitch.

The model 86 clogging indicator provides a visual indication of the filter element.

|                                     |                            |
|-------------------------------------|----------------------------|
| <b>Working fluid</b>                | Oil                        |
| <b>Case</b>                         | Brass                      |
| <b>Cap</b>                          | high performance Polyamid  |
| <b>Visual signal</b>                | White/Red                  |
| <b>Thread (X3)</b>                  | M20x1,5 (other on request) |
| <b>Ambient temperature</b>          | -25°C / +85°C              |
| <b>Fluid temperature</b>            | -10°C / +85°C              |
| <b>Max working pressure</b>         | 350 ÷ 450 bar              |
|                                     | depending on the thread    |
| <b>Action type</b>                  | magnetic                   |
| <b>External pollution situation</b> | grade 2                    |
| <b>Tightening torque max</b>        | 35 Nm                      |
| <b>Operating speed</b>              | 10 bar / 15 sec.           |
| <b>Weight</b>                       | ~ 150 gr                   |