

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product WEICON BR Resin
Code-Nr. 104201

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Bisphenol-A-epoxy resin

Hazardous ingredients

**Hazardous ingredients (continued)**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25 < 35	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
7727-43-7	231-784-4	barium sulphate, natural	25 < 35	

REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
7727-43-7	barium sulphate, natural	01-2119491274-35

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

vomiting

Respiratory complaints

Nausea

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

Metal oxides

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)



Sulphur dioxide (SO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Do not allow to dry out.

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

**WEICON BR Resin****7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Store at +5 till +25 °C.

Keep container tightly closed, store at cool and aired place, open and handle carefully.

Protect from heat and direct solar radiation.

Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
	Barium compounds, soluble(as Ba)	8 hours	0.5		EH40/2005
7727-43-7	Barium sulphate: respirable dust	8 hours	4		EH40/2005
7727-43-7	Barium sulphate: total inhalable dust	8 hours	10		EH40/2005

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		12,25 mg/m3	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,0996 mg/kg	PNEC sediment, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0006 mg/l	PNEC aquatic, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,996 mg/kg	PNEC sediment, freshwater	
		0,018 mg/l	PNEC aquatic, intermittent release	
		11 mg/kg	PNEC Secondary Poisoning	

Additional advice

The statutory local and national regulations have to be observed.

**WEICON BR Resin****8.2. Exposure controls****Respiratory protection**

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

pasty

Colour

dark brown

Odour

uncharacteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	not determined				
melting point	not determined				
Flash point	not applicable			closed cup	
Vapourisation rate	not applicable				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate
Self ignition temperature	not determined				
Lower explosion limit	not applicable				
Upper explosion limit	not applicable				
Vapour pressure	not determined				

**WEICON BR Resin**

	Value	Temperature	at	Method	Remark
Relative density	ca. 1,87 g/cm ³				
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not applicable	20 °C			
Viscosity kinematic	not determined				
Oxidising properties	No information available.				
Explosive properties	not applicable				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Toxic gases/vapours

Metaloxides

Sulphurous oxides (SO_x)**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
Skin irritation	irritant	rabbit		CAS: 25068-38-6
Eye irritation	irritant	rabbit eye		CAS: 25068-38-6
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Harmful if swallowed.

Sensitization through skin contact possible.

Irritates mucous membranes.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

**Additional ecological information**

Value	Method	Remark
AOX		The product contains organically halogen, it can contribute to the adsorbable organic halogen value.

General regulation

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

08 04 09*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 10*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (Epoxy-Harz)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy-resin)	Environmentally hazardous substance, liquid, n.o.s. (epoxy-resin)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.



14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.5

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.