



PART NUMBER

<i>Flange</i>	1 2	ORANGE 3C
3 holes	PK30082 - 100	PK30082 - 500
1" Gas	PK31082 - 100	PK31082 - 500
2 holes	PK32082 - 100	PK32082 - 500

The contact can be converted from N.C. to N.O. by rotating the float upside down

SPDT Contact

PK level sensor can be built by the customer connecting the two parts of the sensor with a brass tube 8 x 6 mm diameter, using the olive fittings provided. The tube must be provided by the customer. Grounding must be fasten by assembling system

For customized version (temperature > 100°C, etc.) please contact our Customer Service.

Use	Mineral oils - Fuels - Water
Fixing	PK 30 3 holes Aluminum flange PK 31 1" gas Aluminum thread PK 32 2 holes Aluminum flange
Float	Foamed nylon (for pressure > 1 bar use NBR float)
Seeger	Phosphorous bronze
Type of contact	Reed N.O./N.C. (SPDT)
Max switch. capacity	80 W (50 W SPDT)
Max switch. current	1 A (1 A SPDT)
Max switch. voltage	250 Vac (220 Vac SPDT)
Protection degree	IP65
with connector according to UNI EN 175301-803 (DIN43650)	
Fluid specific weight	> 0,75
Working temperature	-20°C / +100°C
Weight	~ 220 gr