



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON CBC Hardener
Code-Nr. 101102

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Remark

Do not use for private purposes (household).

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Corr. 1B Eye Dam. 1	H314	
-----------------------------	------	--

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
Skin Sens. 1	H317	
Repr. 1B	H360F	
Aquatic Acute 1		
Aquatic Chronic 1	H410	

Hazard Statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360F	May damage fertility.
H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS05



GHS07



GHS08



GHS09

! Signal word

Danger

Hazard Statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360F	May damage fertility.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P281	Use personal protective equipment as required.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

**! Hazardous ingredients for labeling**

2-N,N-Dimethyl-1,3-diaminopropan, 2,4,6-Tris (dimethylaminomethyl) phenol, 3-Aminomethyl-3,5, 5-trimethylcyclohexylamin, 4,4'-isopropylidenediphenol, Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine, M-phenylenebis (methylamine)

Additional information**Remark**

For industrial use only.

2.3. Other hazards**! Information pertaining to special dangers for human and environment**

Causes burns.

Risk of serious damage to eyes.

Very toxic to aquatic organisms, may cause long-term harmful effects in the aquatic environment.

May impair fertility.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Preparation of different active substances

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
919-30-2	213-048-4	3-aminopropyltriethoxysilane	< 0,5	Acute Tox. 4, H302 / Skin Corr. 1B, H314
157707-73-8	500-382-3	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear, tetraethylenepentamine and triethylenetetramine	40 <= 50	Eye Dam. 1, H318
100-51-6	202-859-9	benzyl-alcohol	6,5 <= 15	Acute Tox. 4, H302; H332 / Eye Irrit. 2, H319
2855-13-2	220-666-8	3-Aminomethyl-3,5, 5-trimethylcyclohexylamin	3,5 < 6,5	Acute Tox. 4, H302, H312 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412
1477-55-0	216-032-5	M-phenylenebis (methylamine)	1,5 < 3,5	Acute Tox. 4, H302, H332 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412 / , EUH071
80-05-7	201-245-8	4,4'-isopropylidenediphenol	1,5 < 3,5	Eye Dam. 1, H318 / Skin Sens. 1, H317 / Repr. 1B, H360F / STOT SE 3, H335 / Aquatic Chronic 2, H411
186321-96-0		Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	15 < 30	Skin Irrit. 2, H315 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Acute 1, H400 M=1 / Aquatic Chronic 1, H410 M=1
109-55-7	203-680-9	2-N,N-Dimethyl-1,3-diaminopropan	0,5 < 1,5	Flam. Liq. 3, H226 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Acute Tox. 4, H302, H312 / Skin Sens. 1, H317 / STOT SE 3, H335
69-72-7	200-712-3	salicylic acid	0,5 < 1,5	Acute Tox. 4, H332 / Eye Dam. 1, H318 /
90-72-2	202-013-9	2,4,6-Tris (dimethylaminomethyl) phenol	0,5 < 1,5	Acute Tox. 4, H302 / Skin Corr. 1C, H314 / Eye Dam. 1, H318 / Skin Sens. 1B, H317 /

REACH

CAS No	Name	REACH registration number
--------	------	---------------------------

**REACH (continued)**

CAS No	Name	REACH registration number
919-30-2	3-aminopropyltriethoxysilane	01-2119480479-24
157707-73-8	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear, tetraethylenepentamine and triethylenetetramine	Polymer
100-51-6	benzyl-alcohol	01-2119492630-38
2855-13-2	3-Aminomethyl-3,5, 5-trimethylcyclohexylamin	01-2119514687-32
1477-55-0	M-phenylenebis (methylamine)	01-2119480150-50
80-05-7	4,4'-isopropylidenediphenol	01-2119457856-23
186321-96-0	Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	01-2119983521-35
109-55-7	2-N,N-Dimethyl-1,3-diaminopropan	01-2119486842-27
69-72-7	salicylic acid	01-2119486984-17
90-72-2	2,4,6-Tris (dimethylaminomethyl) phenol	01-2119560597-27

! Additional advice

SVHC Candidate: CAS 80-05-7

! SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

Seek medical advice immediately.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Remove contaminated clothing immediately, even underwear and shoes.

Seek medical treatment immediately.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

vomiting

Respiratory complaints

Headache

Skin burns

Nausea

skin irritation

Physician's information / possible dangers

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed**! Treatment (Advice to doctor)**

Treat symptoms.

Keep under medical supervision for at least 48 hours.



! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

! Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Wear full protective clothing.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Burns down under strong soot production.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Collect contaminated water / firefighting water separately.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8



! SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Avoid explosion - before application obtain special instructions.

It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Use barrier skin cream.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in original container.

Advice on storage compatibility

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store at 5 to 40°C (=41 to 104°F).

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
100-51-6	benzyl-alcohol	450 mg/m ³	DNEL acute inhalative (systemic)	
		9,5 mg/kg bw/day	DNEL long-term dermal (systemic)	
		90 mg/m ³	DNEL long-term inhalative (systemic)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 28.09.2018 (GB) Version 1.5

WEICON CBC Hardener**DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
		47 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
1477-55-0	M-phenylenebis (methylamine)	0,2 mg/m3	DNEL long-term inhalative (local)	
		1,2 mg/m3	DNEL long-term inhalative (systemic)	
		0,33 mg/kg	DNEL long-term dermal (systemic)	
186321-96-0	Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	3,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		23,5 mg/m3	DNEL long-term inhalative (systemic)	
2855-13-2	3-Aminomethyl-3,5, 5- trimethylcyclohexylamin	20,1 mg/kg bw/day	DNEL acute inhalative (systemic)	
		20,1 mg/m3	DNEL acute inhalative (local)	

PNEC

CAS No	Substance name	Value	Code	Remark
100-51-6	benzyl-alcohol	0,456 mg/kg	PNEC soil, freshwater	
		0,527 mg/kg	PNEC sediment, marine water	
		5,27 mg/kg	PNEC sediment, freshwater	
		1 mg/l	PNEC aquatic, freshwater	
		39 mg/l	PNEC sewage treatment plant (STP)	
		0,1 mg/l	PNEC aquatic, marine water	
1477-55-0	M-phenylenebis (methylamine)	0,094 mg/l	PNEC soil, freshwater	
		0,009 mg/l	PNEC soil, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,43 mg/kg	PNEC sediment, freshwater	
186321-96-0	Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	1,58 mg/l	PNEC sewage treatment plant (STP)	
		0,005 mg/kg	PNEC sediment, marine water	
		0,005 mg/kg	PNEC sediment, freshwater	
		0,00089 mg/ kg	PNEC soil, freshwater	
		0,019 µg/l	PNEC aquatic, marine water	
		0,186 µg/l	PNEC aquatic, freshwater	
2855-13-2	3-Aminomethyl-3,5, 5- trimethylcyclohexylamin	0,06 mg/l	PNEC aquatic, freshwater	
		3,18 mg/l	PNEC sewage treatment plant (STP)	
		5,784 mg/kg	PNEC sediment, freshwater	
		0,578 mg/kg	PNEC sediment, marine water	
		1,121 mg/kg	PNEC soil, freshwater	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 28.09.2018 (GB) Version 1.5

WEICON CBC Hardener

DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		0,006 mg/l	PNEC aquatic, marine water	

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

! Respiratory protection

Selection of the appropriate filter type depends on the quantity and chemicals handled at the workplace. Contact supplier of respiratory protective equipment or more information about filter properties.

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, combination filter A-P1

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

protective shield

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid

Colour

brown

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	ca. 11	20 °C			1:1 in water
boiling point	> 135 °C				
melting point	not determined				
Flash point	> 85 °C				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				



	Value	Temperature	at	Method	Remark
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	ca. 1 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water		20 °C			partially soluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Oxidising properties not determined					
Explosive properties not determined					
9.2. Other information No information available.					

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies.

Reactions with oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Substances to avoid

Alkali (lye)

Acid



oxidising agent

10.6. Hazardous decomposition products

Gases/vapours, toxic

Smoke.

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg			ATE
LD50 acute dermal	> 5000 mg/kg			ATE
LC50 acute inhalation	> 5 mg/l ()		dust/mist	ATE
Skin irritation	corrosive			
Eye irritation	corrosive			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity				-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity	CAS: 80-05-7	Rat	OECD 416	Indications of toxic effects are available from reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Toxicity test (Additional information)

Indications of genotoxic effects at humans are available from reproduction studies in animals.

Experiences made from practice

Risk of strong health injuries in case of long-term exposition.

Corrosive effect on skin and mucous membrane.

Sensitization through inhalation possible.

Risk of strong eye injuries.

Inhalation causes headache/nausea.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 1,86 mg/l (96 h)	Fish	OECD 203	CAS: 186321-96-0
Daphnia	EC 50 0,705 mg/l (48 h)	Daphnia magna	OECD 202	CAS: 186321-96-0
Algae	ErC50 0,186 mg/l (72 h)	Selenastrum capricornutum	OECD 201	CAS: 186321-96-0
Bacteria	EC50 157,6 mg/l (3 h)	activated sludge	OECD 209	CAS: 186321-96-0

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	9 % (28 d) CAS: 186321-96-0		OECD 301 D	not readily degradable
Degradability	8 % (28 d) CAS: 2855-13-2		67/548/EWG, Annex V,C.4.E	not readily degradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Very toxic to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

! SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

! Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	2735	2735	2735
14.2. UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine)	Amines, liquid, corrosive, n.o. s. (Isophorone diamine)
14.3. Transport hazard class(es)	8	8	8
14.4. Packing group	II	II	II
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 8

tunnel restriction code E

Classification code C7

Marine transport IMDG

MARINE POLLUTANT

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

! VOC standard

VOC content 0 %

Remark

Request data separately.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**Training advice**

The product is intended only for the industrial/professional use.

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.



Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.4

EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H302,	-?-
H302,	-?-
H302;	-?-
H332	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.