

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product WEICON CBC Resin
Code-Nr. 101101

**1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS05



GHS07



GHS09

Signal word

Danger

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

1,4-Bis(2,3-epoxypropoxy)butane, bis-[4-(2,3-epoxypropoxy)phenyl]propane, Reaction Product of Phenol-Formaldehyde Novolac and Epichlorohydrin

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Information pertaining to special dangers for human and environment

Risk of serious damage to eyes.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 02.11.2018 (GB) Version 8.8

WEICON CBC Resin

Description

Preparation of different active substances

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
28064-14-4	polymer	Reaction Product of Phenol-Formaldehyde Novolac and Epichlorohydrin	10 < 20	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
2425-79-8	219-371-7	1,4-Bis(2,3-epoxypropoxy)butane	3 < 10	Acute Tox. 4, H302, H312 / Skin Irrit. 2, H315 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412 / Acute Tox. 4, H332
1675-54-3	216-823-5	bis-[4-(2,3-epoxypropoxy)phenyl]propane	25 < 30	Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411 M=0

REACH

CAS No	Name	REACH registration number
28064-14-4	Reaction Product of Phenol-Formaldehyde Novolac and Epichlorohydrin	not subject to registration
2425-79-8	1,4-Bis(2,3-epoxypropoxy)butane	01-2119494060-45
1675-54-3	bis-[4-(2,3-epoxypropoxy)phenyl]propane	01-2119456619-26

Additional advice

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorohydrin

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

Seek medical treatment immediately.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Remove contaminated clothing immediately, even underwear and shoes.

Seek medical treatment immediately.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Give water to drink in small sips.

Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

Unconsciousness

Coughing

vomiting

Respiratory complaints

Headache

Allergic symptoms

Skin burns

skin irritation



Physician's information / possible dangers

allergic reactions

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Metal oxides

Danger of bursting

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

halogenated compounds

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Keep people away and stay on the upwind side.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature between 2°C to 40°C

Recommended storage temperature: room temperature.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl] propane	12,25 mg/m ³	DNEL long-term inhalative (local)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 8.8

WEICON CBC Resin

DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		12,25 mg/m ³	DNEL acute inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid

Colour

grey

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	6	20 °C			500 g/l
boiling point	> 200 °C				
melting point	not determined				
Flash point	121 °C			DIN 51758	Pensky-Martens Closed Cup
Vapourisation rate	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 8.8

WEICON CBC Resin

	Value	Temperature	at	Method	Remark
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not applicable				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 0,2 Pa	20 °C			
Relative density	1,74 g/cm ³	25 °C			
Vapour density	not determined				
Solubility in water		20 °C			insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	70 - 90 Pa*s	25 °C			
Viscosity kinematic	not determined				
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Alkali (lye), concentrated

Acid, concentrated

Oxidising agent, strong

10.6. Hazardous decomposition products

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Halogenated hydrocarbons

Aluminium oxide fume

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg		estimate	ATE
LD50 acute dermal	> 2000 mg/kg		estimate	ATE
LC50 acute inhalation	> 5 mg/l (4 h)	estimate	dust/mist	ATE
Skin irritation	irritant	rabbit		
Eye irritation	risk of strong eye injuries	rabbit eye		
Skin sensitization	sensitizing	Guinea pig		

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity	NOAEL 50 mg/kg Repeated Dose 90-Day Oral Toxicity Study in Rodents		OECD 408	-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity	NOEL 540 mg/kg	Rat	OECD 416	No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

May irritate the mucosae.

Sensitization through skin contact possible.

Allergic reactions possible (analogy-reasons).



Risk of strong eye injuries.
Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.
Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 1,5 mg/l (96 h)	Oncorhynchus mykiss	OECD 203	CAS: 1675-54-3
Daphnia	EC50 1,7 mg/l (48 h)	Daphnia sp.	OECD 202	CAS: 28064-14-4
Algae	EC50 9,4 mg/l (72 h)	Green algae	EPA CFR	CAS: 1675-54-3
Bacteria	IC50 > 100 mg/l (3 h)	activated sludge		CAS: 28064-14-4

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	5 % (28 d) CAS: 1675-54-3		OECD 301 F	not readily degradable

12.3. Bioaccumulative potential

No bioaccumulation

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Toxic to aquatic life with long lasting effects.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (BISPHENOL A EPOXY Harz Mischung)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN MIXTURE)	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN MIXTURE)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Special provisions 274 335 601

Classification code M6

Marine transport IMDG

MARINE POLLUTANT

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 0 %**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 8.8

WEICON CBC Resin

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.0

H302,	-?-
H312	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.