

**Copper Spray****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Copper Spray
Code-Nr. 111010

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Eye Irrit. 2	H319	
STOT SE 3	H336	
Aquatic Acute 1		
Aquatic Chronic 1	H410	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.

Copper Spray

- H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS02



GHS07



GHS09

! Signal word

Danger

Hazard Statements

- H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P391 Collect spillage.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

acetone, ethyl-acetate, Hydrocarbons, C9, aromatics

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
Description

Copper spray based on synthetic resin cement, solvent and pigments. Propellant: propane / butane

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	20 - 25	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
106-97-8	203-448-7	butane	10 < 20	Flam. Gas 1, H220 / Press. Gas
141-78-6	205-500-4	ethyl-acetate	10 - 20	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
74-98-6	200-827-9	propane	10 < 20	Flam. Gas 1, H220 / Press. Gas, H280
64742-95-6	918-668-5	Hydrocarbons, C9, aromatics	2,5 < 10	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / STOT SE 3, H336 / Aquatic Acute 2, H411
		Kupferflocken (mit einem Überzug aus aliphatischer Säure)	2,5 < 10	Acute Tox. 4, H302 M=1 / Acute Tox. 3, H331 / Eye Irrit. 2, H319 / Aquatic Acute 1, H400 M=10 / Aquatic Chronic 1, H410 M=1

REACH

CAS No	Name	REACH registration number
67-64-1	acetone	01-2119471330-49
106-97-8	butane	01-2119474691-32
141-78-6	ethyl-acetate	01-2119475103-46
74-98-6	propane	01-2119486944-21
64742-95-6	Hydrocarbons, C9, aromatics	01-2119455851-35
	Kupferflocken (mit einem Überzug aus aliphatischer Säure)	Index Nr: 029-019-01-X

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.



Copper Spray

In case of ingestion

Do not induce vomiting.
Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam
ABC powder
Carbon dioxide
sand

Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

Danger of bursting
In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Vapours are heavier than air and will spread on the ground.
Cool endangered containers with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale dust/fumes/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Store at +5 till +25 °C.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
7440-50-8	Copper: fume	8 hours	0.2		EH40/2005
		Short-term	2		
7440-50-8	Copper: dusts and mists (as Cu)	8 hours	1		EH40/2005



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 24.05.2019 (GB) Version 8.9

Copper Spray**Ingredients with occupational exposure limits to be monitored (continued)**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
141-78-6	Ethyl acetate	8 hours Short-term		200 400	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
67-64-1	acetone	8 hours	1210	500	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
141-78-6	ethyl-acetate	734 mg/m ³	DNEL long-term inhalative (local)	
		63 mg/kg	DNEL long-term dermal (systemic)	
		1468 mg/m ³	DNEL acute inhalative (systemic)	
		1468 mg/m ³	DNEL acute inhalative (local)	
64742-95-6	Hydrocarbons, C9, aromatics	103 mg/m ³	DNEL long-term inhalative (systemic)	
		25 mg/kg	DNEL long-term dermal (systemic)	
67-64-1	acetone	2420 mg/m ³	DNEL acute inhalative (local)	
		1210 mg/m ³	DNEL long-term inhalative (systemic)	
		186 mg/kg	DNEL long-term dermal (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
141-78-6	ethyl-acetate	0,024 mg/l	PNEC aquatic, marine water	
		0,24 mg/l	PNEC aquatic, freshwater	
		0,34 mg/kg	PNEC sediment, freshwater	
		0,115 mg/kg	PNEC sediment, marine water	
67-64-1	acetone	3,04 mg/kg	PNEC sediment, marine water	
		1,06 mg/l	PNEC aquatic, marine water	
		30,4 mg/kg	PNEC sediment, freshwater	
		10,6 mg/l	PNEC aquatic, freshwater	

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

**Copper Spray****Eye protection**

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

copper-coloured

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	-44 °C				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	1,5 Vol-%				
Upper explosion limit	13 Vol-%				
Vapour pressure	not determined				
Relative density	not determined				
Vapour density	not determined				
Solubility in water					immiscible
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P OW)	not determined				

**Copper Spray**

	Value	Temperature	at	Method	Remark
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Formation of explosive gas/air mixtures.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg		estimate	ATE
LD50 acute dermal	> 2000 mg/kg	rabbit		Acetone
LC50 acute inhalation	800000 ppm (0,25 h)	rat		Propane

**Copper Spray**

	Value/Validation	Species	Method	Remark
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Vapours may cause dizziness, headaches and tiredness

Experiences at humans: may cause hypersensitivity reactions on skin in case of persons suffering from hypersensitivity.

Risk of strong eye injuries.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Very toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

**Copper Spray****SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

16 05 04*

Name of waste

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS (Copper)	AEROSOLS (Copper)	Aerosols, flammable (Copper)
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 85,9 %

VOC value 732,3 g/L



15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.8

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.