

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Name of product	Easy-Mix RK-7000 Hardener Code-Nr. 105652
1.2. Relevant identified uses of the substance or mixt Recommended intended purpose(s) 2-Component Epoxy Resin - Hardener Component	ure and uses advised against
1.3. Details of the supplier of the safety data sheet	
Distributor	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244 E-Mail : msds@weicon.de Internet : www.weicon.de
Advice	Produktsicherheit / Product-Safety-Department Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person): msds@weicon.de
1.4. Emergency telephone number	
	EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
Manufacturer	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster
1.4. Emergency telephone number	
	GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h): Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes a categories	nd Hazard	Hazard Statements	Classification procedure
Flam. Liq. 2		H225	
Skin Irrit. 2		H315	
Skin Sens. 1		H317	
STOT SE 3		H335	
Hazard Stateme H225		nable liquid and vapou	r.
H315	Causes skin	irritation.	
H317	May cause a	an allergic skin reactior	٦.
H335	•	espiratory irritation.	



2.2. Label elements Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

Signal word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary Statements

P102	Keep out of reach of children.
P210 P233 P243 P261 P264 P271 P272	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.
P302 + P352 P303 + P361 + P353 P304 + P340 P312 P332 + P313 P333 + P313 P362 P363 P370 + P378	 IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing. Wash contaminated clothing before reuse. In case of fire: Use foam for extinction.
P403 + P233 P403 + P235 P405	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

methyl methacrylate

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Preparation of different active substances

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
80-62-6	201-297-1	methyl methacrylate	50 <= 75	Flam. Liq. 2, H225 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
	400-160-5	fatty acids, tall-oil, reaction products with iminodiethanol and boric acid	< 1	Skin Irrit. 2, H315 / Aquatic Chronic 2, H411
27138-31-4	248-258-5	Oxydipropyldibenzoat	< 10	Aquatic Chronic 3, H412
34562-31-7	252-091-3	3,5-diethyl-1,2-dihydro-1-phenyl-2- propylpyridine	1 < 3	Acute Tox. 4, H302, H312 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Aquatic Chronic 4, H413
107-98-2	203-539-1	1-methoxy-2-propanol	< 0,1	Flam. Liq. 3, H226 / STOT SE 3, H336
34590-94-8	252-104-2	(2-Methoxymethylethoxy)-propanol	< 0,1	nicht eingestuft
REACH				
CAS No	Name			REACH registration number
80-62-6	methyl metha	acrylate		01-2119452498-28
	fatty acids, tall-oil, reaction products with iminodiethanol and boric acid			not subject to registration
27138-31-4	Oxydipropyldibenzoat			01-2119529241-49
34562-31-7	3,5-diethyl-1,	3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine		01-2120769712-47
107-98-2	1-methoxy-2-	propanol		01-2119457435-35
34590-94-8	(2-Methoxym	iethylethoxy)-propanol		01-2119450011-60

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air. In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting. Call for a doctor immediately. Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms vomiting Respiratory complaints Allergic symptoms Confusion skin irritation



Physician's information / possible dangers allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam Dry powder Carbon dioxide Dry sand water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Metal oxides In case of fire formation of dangerous gases possible. Nitrogen oxides (NOx) Carbon monoxide (CO) Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters. Do not discharge into the drains or bodies of water.. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust). After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.



6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Ventilate closed rooms at ground level. Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs. Remove soiled or soaked clothing immediately. Wash hands and skin before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking Protect from heat and sunlight. Take precautionary measures against static discharges. Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store with acids or alkalies. Do not store together with animal feedstuffs. Do not store together with food. Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place. Protect from heat and direct solar radiation. Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
34590-94-8	(2-Methoxymethylethoxy) propanol	8 hours	308	50	EH40/2005
107-98-2	1 -Methoxypropan-2-ol	8 hours Short-term	375 560	100 150	EH40/2005
80-62-6	Methyl methacrylate	8 hours Short-term	208 416	50 100	EH40/2005



Safety Data Sheet according to Regulation (EC)

 No. 1907/2006 (REACH)

 Printed
 05.08.2019

 revision
 30.07.2018 (GB) Version 9.0

 Fasy Mix PK 7000 Hardonor

Easy-Mix RK-7000 Hardener

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
107-98-2	1-methoxy-2-propanol	8 hours	375	100	skin
		Short-term	568	150	
80-62-6	methyl-methacrylate	8 hours		50	
DNEL-/PNEC DNEL worke		Short-term		100	
CAS No	Substance name	Value	Code	F	Remark
27138-31-4	Oxydipropyldibenzoat	10 mg/kg bw/day	DNEL long-term dermal (systemic)		
		170 mg/kg bw/day	DNEL acute dermal, sho (systemic)	rt-term	
		8,8 mg/m3	DNEL long-term inhalativ (systemic)	'e	
PNEC					
CAS No	Substance name	Value	Code	F	Remark
27138-31-4	Oxydipropyldibenzoat	1,49 mg/kg	PNEC sediment, freshwa	ater	
		0,00037 mg/l	PNEC aquatic, marine w	ater	
		1 mg/kg	PNEC soil, freshwater		
		0,0037 mg/l	PNEC aquatic, freshwate	er	
		10 mg/kg	PNEC sewage treatment	plant (STP)	
		0,149 mg/kg	PNEC sediment, marine	water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.



SECTION 9: Physical and chemical properties

Appearance pasty		colour /hitish		Odour pungent	
Odour threshold not determined					
Important health, safety and	d environmental i	nformation			
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	10 °C			closed cup	
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	0,97 - 1,01 g/ cm3	20 °C			
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	> 0,4	40 °C			



Oxidising properties No information available.

Explosive properties No information available.

9.2. Other information No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability No information available.

10.3. Possibility of hazardous reactions

Reactions with oxidising agents. Reactions with reducing agents. If heating up polymerisation.

10.4. Conditions to avoid

Keep away from heat. Evolution of heat.

10.5. Incompatible materials

Substances to avoid Oxidising agent, strong Reducing agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide. Nitrous oxides (NOx) Toxic gases/vapours Metaloxides

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	97023 mg/kg			ATE
LD50 acute dermal	65880 mg/kg			ATE
LC50 acute inhalation	> 200 mg/l (4 h)	rat		CAS: 27138-31-4
Skin irritation	irritant			



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Printed 05.08.2019 revision 30.07.2018 (GB) Version 9.0

Easy-Mix RK-7000 Hardener

	Value/Validation	Species	Method	Remark
Eye irritation	low irritant - no labeling duty			
Skin sensitization	sensitizing			
Subacute Toxicity - (Carcinogenicity			
	Value	Species	Method	Validation
Chronic Toxicity	NOAEL 1000 mg/kg (90 d) Repeated Dose 90-Day Oral Toxicity Study in Rodents			-
Mutagenicity				No experimental information on genotoxicity in vivo available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation. Sensitization through skin contact possible. Irritates mucous membranes.

Additional information

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded. The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicolog	Value	Species	Method	Validation
Fish	LC50 130000 Mikro-g/l (96 h)	Pimephales pro	omelas	CAS: 80-62-6
Daphnia	EC 50 19,3 mg/l (48 h)	Daphnia magna	a	CAS: 27138-31-4
Algae	EC50 4,9 mg/l (72 h)	Green algae		CAS: 27138-31-4
12.2. Persiste	ence and degradability Elimination rate	Method of analysis	Method	Validation
Degradability	87 % (28 d)			readily degradable
	CAS: 27138-31-4			

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil



No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recommendations for the product

Remove in accordance with local official regulations. Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1133	1133	1133
14.2. UN proper shipping name	ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	II	II	II
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Land and inland navigation transport ADR/RID Hazard label(s) 3 tunnel restriction code D/E Special provisions 640D

Classification code F1



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard	
VOC content	50,7 %
VOC value	ca.510 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous

substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.9

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302, -?-
- H318 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.