

Temperature switch**ERNO & IRNO**

Surface mounting with 6mm diameter hole.
Ideal for engines, pumps & gearboxes etc.

FEATURES

- Insulated or earth return
- Die-cast body
- 6mm Ø hole for surface mounting

Part Numbers

TS/ERNO/100

TS/ERNO/107

TS/IRNO/100

TS/IRNO/105

TS/IRNO/120

Other temperatures available on request.
(minimum 50 pcs order quantity)

See [DataFax 2501](#) for threaded brass models

**Technical data**

Max. switching Temperature	170°C
Max. working Temperature	210°C
Temperature Differential	11°C
Tolerance	± 3°C
Body Material	Die-cast aluminium with 6mm Ø mounting hole
Contacts	Silver plated
Contact Rating	12V/16A; 24V/12A; 250Va/10A
Electrical Rating	50,000 cycles @ 12v 100,000 cycles @ 250v

PRESSURE-VACUUM-LEVEL LTD

Unit 9, Lexden Lodge Industrial Estate, Jarvis Brook,
Crowborough, East Sussex, TN6 2NQ U.K.

Tel: +44(0)1892 66 44 99 Fax: +44(0)1892 66 36 90

Web: www.pvl.co.uk Email: info@pvl.co.uk

PVL
Switched on to Industry