

Product Information

Conductivity measuring device GMH 5430 / 5450



- Made in Germany
- Waterproof and impact-resistant
- Conductivity, resistance, salinity, TDS
- Large double display with backlighting
- Automatic adjustment with reference solutions including test report
- perfect for quality assurance

Features

Conductivity and concentration monitoring in aquaculture, aquariums and in drinking water supply. Numerous agricultural applications (e.g. soil studies). Also suitable for quality assurance and control in industrial applications and in food production. Especially well-suited for investigation at water treatment, e.g. in humidification systems and for countless cleaning processes. Also suitable for medical, pharmaceutical and industrial laboratories. Designed for harsh environments: Impact-resistant and protected from water, the device even floats.

Technical data

Measuring ranges	
Number of measuring ranges	5
Smallest measuring range	0.000..5.000 µS/cm * or 0.0..500.0 µS/cm **
Largest measuring range	0..5000 µS/cm * or 0...1000 mS/cm **
Spec. resistance	0.005..500.0 kOhm * cm (depending on cell constants)
TDS	0..5000 mg/l (depending on cell constants)
Salinity	0.0..70.0 (g salt / kg water)
Temperature	-5.0..+100.0 °C, Pt1000 or NTC 10 k
Supported cell constants	4.000..15.000 / cm - 0.4000..1.5000 / cm - 0.04000..0.15000 / cm - 0.004000..0.015000 / cm
Accuracy (at nominal temperature 25 °C)	
Conductivity	±0.5 % of MW ±0.1 % FS (measuring cell dependent)
Temperature	0.2 K

Connections	
Conductivity, temperature	1 x 7-pole bayonet connection for connection of various measuring cells, supported temperature sensors Pt1000 or NTC 10 k
Interface / ext. power supply	4-pole bayonet connection for serial interface and supply (with accessories: USB adapter USB 5100)
Analogue output (only GMH 5450)	0..1 V, freely scalable, connection via 4-pole bayonet jack, 13 bit resolution, 0.05 % accuracy at nominal temperature
Data logger (only GMH 5450)	Cyclical: 10,000 data records, Variable cycle: 1 s..60 min Single: 1,000 data records (with measuring point entry, 40 adjustable measuring point texts or measuring point numbers)
Display	4 ½ digit 7-segment, illuminated (white)
Operating conditions	Device: -25..+50 °C
Storage temperature	-25 ... +70 °C
Backlighting	Adjustable lighting duration (off, 5 s ... 2 min)
Current supply	2 x AAA batteries, power consumption: 6.25 mA
Battery life	approx. 160 h (without lighting)
Protection rating	IP65 / IP67
Housing	Impact-resistant ABS, with stand/suspension clip
Dimensions	160 x 86 x 37 mm (H x W x D) incl. silicone protective cover
Weight	approx. 250 g incl. battery and protective cover

Depending on cell constant of the LF electrode
 * Cell constant 0.01 / cm ** Cell constant 0.1..1.2 / cm (standard)

Additional functions

Adjustment: Manual or automatic cell constant via reference solutions.

Automatic temperature compensation: The conductivity depends heavily on the temperature so that it is only applicable for the relevant temperature. Therefore, the device offers the option of compensating the conductivity to a reference temperature (adjustable to 20 °C or 25 °C).

Supported compensation types:

- nLF: Non-linear function of natural water according to DIN EN27888 (ISO 7888, reference temperature 25 °C)
- Lin: Adjustable linear compensation
- off: No compensation

Salinity determination: Salinity is the sum of the concentration of all dissolved salts in sea water. The variable is specified in g / kg (corresponding to PSU = Practical Salinity Unit).

TDS determination (total dissolved solids): Total dissolved solids is the designation for the mass concentration of substances dissolved in a liquid. The variable is specified in mg / l.

GLP (Good Laboratory Practice): Variable calibration interval, GMH 5450: Calibration memory for last 16 calibrations

Scope of delivery

- Device, K 50 BL, battery, test report, operating manual, data logger, electrode not included

Product Information

Accessories

GKL 100, art. no. 601396
Conductivity control solution
(100 ml bottle with 1413 µS/cm, in accordance with DIN EN 27888)

GKL 101, art. no. 601398
Conductivity control solution
(250 ml bottle with 84 µS/cm)

GKL 102, art. no. 601400
Conductivity control solution
(100 ml bottle with 50 mS/cm)

EBS 20M, art. no. 601158
Software for long-term monitoring

GSOFT 3050, art. no. 601336
Software for operation of logger devices

USB 5100, art. no. 601095
galvanically isolated interface converter with device power supply via USB

GNG 5 / 5000, art. no. 602287
Plug-type mains adapter 5 V DC, suitable for GMH 5000 series

GKK 5001, art. no. 611606
with cut-outs for 1 device of the GMH 5xxx-/7500 series and accessories for water analysis (395 x 295 x 106 mm)

Measuring cells

LF 200 RW, art. no. 602841
2-pole stainless steel/Peek, Ø 12 mm, cable length 1 m
Pure and purest water up to max. 200.0 µS/cm

LF 210, art. no. 602969
2-pole glass/platinum, Ø 12 mm, cable length 1 m
for alcohol, benzine, diesel, paint 0 .. 1000 µS/cm

LF 400, art. no. 602968
4-pole graphite/plastic, Ø 12 mm, economy, cable length 2 m
universal use with max. 200 mS/cm

LF 425, art. no. 602840
4-pole graphite/plastic, Ø 16 mm, wide-range, cable length 1 m
Our best: up to 1000 ms/cm with the highest accuracy

- **Additional accessories on request or in our catalogue**

Ordering code

1.
GMH 5430 -

1. Option	
	Device alone (without electrode)
200-L01	Device, LF 200 RW measuring cell, 2-pole stainless steel/Peek, 1 m
210-L01	Device, LF 210 measuring cell, 2-pole glass/platinum, 1 m
400-L02	Device, LF 400 measuring cell, 4-pole graphite economy, 2 m
425-L01	Device, LF 425 measuring cell, 4-pole graphite wide-range, 1 m
Set	Device, LF425-L01, GKK 5001

1.
GMH 5450 -

1. Option	
	Device alone (without electrode)
200-L01	Device, LF 200 RW measuring cell, 2-pole stainless steel/Peek, 1 m
210-L01	Device, LF 210 measuring cell, 2-pole glass/platinum, 1 m
400-L02	Device, LF 400 measuring cell, 4-pole graphite economy, 2 m
425-L01	Device, LF 425 measuring cell, 4-pole graphite wide-range, 1 m
Set	Device, LF425-L01, GKK 5001