



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Easy-Mix HT 180 Resin
Code-Nr. 106541

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Corr. 1B	H314	
---------------	------	--

Eye Dam. 1		
------------	--	--

Skin Sens. 1	H317	
--------------	------	--

Hazard Statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]


GHS05



GHS07

Signal word

Danger

Hazard Statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary Statements

P102 Keep out of reach of children.

P260 Do not breathe vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/eye protection.

P301 + P330 + IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P331

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P353

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P338

P310 Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

2-Ethyl-4-methylimidazol, 2-Methylpentan-1,5-diamin, 2,4,6-tris(dimethylaminomethyl)phenol, 3,3'-Oxybis(ethylenoxy) bis(propylamin), Bis((dimethylamino)methyl)phenol

2.3. Other hazards
Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	5 < 10	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
71074-89-0	275-162-0	Bis((dimethylamino)methyl)phenol	1 < 2,5	Skin Corr. 1B, H314

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
4246-51-9	224-207-2	3,3'-Oxybis(ethylenoxy)bis(propylamin)	10 - 15	Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317
931-36-2	213-234-5	2-Ethyl-4-methylimidazol	2,5 < 3	Acute Tox. 4, H302 / Skin Irrit. 2, H315 / Eye Dam. 1, H318 / Skin Sens. 1B, H317
15520-10-2	239-556-6	2-Methylpentan-1,5-diamin	1 < 2,5	Acute Tox. 4, H302, H312 / Acute Tox. 4, H332 / Skin Corr. 1A, H314 / Eye Dam. 1, H318 / STOT SE 3, H335
822-36-6	212-497-3	4-Methylimidazol	0,3 < 0,5	Acute Tox. 3, H301, H331 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Carc. 2, H351 / STOT SE 335, H335 /
60676-86-0	262-373-8	Siliciumdioxid, glasartig	10 - 15	

REACH

CAS No	Name	REACH registration number
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	01-2119560597-27
71074-89-0	Bis((dimethylamino)methyl)phenol	not subject to registration
4246-51-9	3,3'-Oxybis(ethylenoxy)bis(propylamin)	01-2119963377-26
931-36-2	2-Ethyl-4-methylimidazol	01-2119980935-21
15520-10-2	2-Methylpentan-1,5-diamin	01-2119976310-41
822-36-6	4-Methylimidazol	01-2119948594-25
60676-86-0	Siliciumdioxid, glasartig	not subject to registration

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.
Refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with plenty of water.
Refer for medical treatment.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Seek medical advice.
Do not induce vomiting.
Call for a doctor immediately.
Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed
Physician's information / possible symptoms

vomiting
Skin burns
Gastrointestinal complaints

Physician's information / possible dangers

allergic reactions
Causes serious eye damage.



4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry fire-extinguishing substance

ABC powder

Carbon dioxide

water mist

Unsuitable extinguishing media

Halone

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Ammonia

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Formaldehyde vapours

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

For emergency responders

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Ventilate area concerned

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Ensure sufficient ventilation.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from atmospheric moisture and water

Protect from heat and direct solar radiation.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
60676-86-0	Silica, fused respirable dust	8 hours	0.08		EH40/2005

DNEL-/PNEC-values

DNEL worker

CAS No	Substance name	Value	Code	Remark
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,31 mg/m3	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,2 mg/l	PNEC sewage treatment plant (STP)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 10.07.2018 (GB) Version 1.4

Easy-Mix HT 180 Resin

DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		0,084 mg/l	PNEC aquatic, freshwater	
		0,0084 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, filter A

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

viscous

Colour

yellowy-brown

Odour

similar to amine

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	132,5 °C		ca. 1,3 hPa		Calculated out of the components.
melting point	not determined				
Flash point	> 93,4 °C			closed cup	
Vapourisation rate	1				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 10.07.2018 (GB) Version 1.4

Easy-Mix HT 180 Resin

	Value	Temperature	at	Method	Remark
Ignition temperature	not determined				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 10 hPa	20 °C			
Relative density	1,13 g/cm ³	25 °C			
Vapour density	> 1	20 °C			
Solubility in water					more or less insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	> 10000 mm ² /s	40 °C			
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

Reactions with peroxides and other radical components.

10.4. Conditions to avoid

Keep away from heat.

Moisture.

**10.5. Incompatible materials****Substances to avoid**

strong bases
Hydrofluorocarbons
Alkali (lye)
Peroxide
Acid
Oxidising agent
Moisture.

10.6. Hazardous decomposition products

Hydrogen cyanide (hydrocyanic acid)
Carbon monoxide and carbon dioxide.
Nitrous oxides (NOx)
Formaldehyde
Ammonia

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	ca. 731 mg/kg	rat	OECD 401	CAS: 931-36-2
LD50 acute dermal	440 mg/kg	rabbit		CAS: 822-36-6
LC50 acute inhalation	> 0,03 mg/l (8 h)	rat	OECD 403	CAS: 931-36-2
Skin irritation	corrosive			
Eye irritation	corrosive			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Toxicity test (Additional information)

Substance has no mutagen activity (Ames test).

Experiences made from practice

Acute Tox: Beobachtungen ergaben keine Beeinträchtigungen. Daher ergaben keine Einstufung.

Sensitization through skin contact possible.

Causes corrosions.

Irritates respiratory tract.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 180 - 240 mg/l (96 h)	Oncorhynchus mykiss		CAS: 90-72-2
Daphnia	NOEC 4,16 mg/l (21 d)	Daphnia magna	OECD 211	CAS: 15520-10-2
Algae	NOEC 10 mg/l (72 h)	Pseudokirchneriella subcapitata	OECD 201	CAS: 15520-10-2
Bacteria	EC50 30 mg/l (18 h)	Pseudomonas putida		CAS: 15520-10-2

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	< 10 % (60 d) CAS: 4246-51-9		OECD 301 B	not readily degradable
Degradability	100 % (28 d) CAS: 15520-10-2		OECD 301 D	Biodegradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3267	3267	3267
14.2. UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ALIPHATIC AMINE)	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ALIPHATIC AMINE)	Corrosive liquid, basic, organic, n.o.s. (ALIPHATIC AMINE)
14.3. Transport hazard class(es)	8	8	8
14.4. Packing group	III	III	III
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 8

tunnel restriction code E

Classification code C7

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.3

H301,	-?-
H302	Harmful if swallowed.
H302,	-?-
H312	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).