

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** Primer K 200  
Code-Nr. 135502

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

to be used as surface preconditioning

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 2	H225	
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
STOT SE 3	H336	
Asp. Tox. 1	H304	
Aquatic Chronic 3	H412	

**Hazard Statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS08

### Signal word

Danger

### Hazard Statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P370 + P378	In case of fire: Use foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

**Hazardous ingredients for labeling**

Hydrocarbons, C6-C9, propan-2-ol

**2.3. Other hazards****Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****! Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	50 - 75	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
110-54-3	203-777-6	n-hexane	< 1	Flam. Liq. 2, H225 / Repr. 2, H361f / Asp. Tox. 1, H304 / STOT RE 2, H373 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411
546-68-9	208-909-6 921-024-6	Tétraisopropanolate de titane Kohlenwasserstoffe, C6-C7	< 2 15 < 25	Eye irrit. 2, H319 / Flam. Liq. 3, H226 Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336

**REACH**

CAS No	Name	REACH registration number
67-63-0	propan-2-ol	01-2119457558-25
110-54-3	n-hexane	01-2119480412-44
546-68-9	Tétraisopropanolate de titane Kohlenwasserstoffe, C6-C7	01-2119967389-17 01-2119475515-33

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

Dab affected skin part with a cotton ball or cellulose and wash it afterwards with plenty of water and a mild cleaner.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.



---

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

vomiting  
Respiratory complaints  
Nausea  
skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

**Treatment (Advice to doctor)**

If swallowed or in the event of vomiting, risk of entering the lungs.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam  
Dry powder  
Carbon dioxide  
Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)  
Carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.  
Use breathing apparatus if exposed to vapours/dust/aerosol.

**6.2. Environmental precautions**

Do not discharge into the drains or bodies of water..  
Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Take up mechanically and send for disposal.

**Additional Information**

Sort out leaky cans and dispose according to regulations.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.  
Provide good room ventilation even at ground level (vapours are heavier than air).

**General protective measures**

Do not inhale vapours.

Avoid contact with eyes and skin

**Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

The heavy vapours may bridge a long distance to source of ignition.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Prevent penetration into the ground.

Keep only in original container.

**Advice on storage compatibility**

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

**Further information on storage conditions**

Keep container tightly closed, store at cool and aired place, open and handle carefully.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
110-54-3	n-hexane	8 hours	72	20	EH40/2005
67-63-0	propan-2-ol	8 hours Short-term	999 1250	400 500	EH40/2005

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
110-54-3	n-hexane	8 hours	72	20	

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
	Kohlenwasserstoffe, C6-C7	2035 mg/m3	DNEL long-term inhalative (systemic)	
110-54-3	n-hexane	75 mg/m3	DNEL long-term inhalative (systemic)	
67-63-0	propan-2-ol	500 mg/m3	DNEL long-term inhalative (systemic)	
		888 mg/kg bw/day	DNEL long-term dermal (systemic)	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

liquid

**Colour**

colourless

**Odour**

solvent-like

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	60 °C				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.08.2018 (GB) Version 8.8

**Primer K 200**

	Value	Temperature	at	Method	Remark
<b>melting point</b>	not determined				
<b>Flash point</b>	-30 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	> 200 °C				
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	1,1 Vol-%				
<b>Upper explosion limit</b>	12 Vol-%				
<b>Vapour pressure</b>	246 hPa	20 °C			
<b>Relative density</b>	0,77 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					partially soluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined				
<b>Solvent content</b>	98,2 %				

**Oxidising properties**

No information available.

**Explosive properties**

Explo. Gr.: IIA (gem. 94/9/EG ATEX)

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidising agents.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Alkali (lye)

Acid

oxidising agent

**10.6. Hazardous decomposition products**

Carbon monoxide

Carbon dioxide

Toxic gases/vapours

May form propan-2-ol in contact with water / moisture.

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant			
<b>Skin sensitization</b>	non-sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Experiences made from practice**

Vapours may cause dizziness, headaches and tiredness

Inhalation can cause damage to the respiratory tract or lungs.





Irritates eyes and skin.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

---

**SECTION 12: Ecological information**

**12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

No information available.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

**General regulation**

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

---

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Waste code No.**

08 04 09\*

**Name of waste**

waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10

waste adhesives and sealants other than those mentioned in 08 04 09

15 01 04

metallic packaging

15 01 10\*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	1993	1993	1993
<b>14.2. UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (ISOPROPYLALKOHOL, HEPTAN, MISCHUNG)	FLAMMABLE LIQUID, N.O.S. (ISOPROPYLALCOHOL, HEPTANES, MIXTURE)	Flammable liquid, n.o.s. (ISOPROPYLALCOHOL, HEPTANES, MIXTURE)
<b>14.3. Transport hazard class(es)</b>	3	3	3
<b>14.4. Packing group</b>	II	II	II
<b>14.5. Environmental hazards</b>	No	No	No

**14.6. Special precautions for user**

Caution: FLAMMABLE LIQUID

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 3

tunnel restriction code D/E

Special provisions 640D

Classification code F1

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 98,2 %**VOC value** 756,3 g/L**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed

05.08.2019

revision

02.08.2018 (GB) Version 8.8

**Primer K 200**

---

- H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
H411 Toxic to aquatic life with long lasting effects.