



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Repair Stick Plastic
Code-Nr. 105360

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resins

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Sens. 1	H317	
Aquatic Chronic 3	H412	

Hazard Statements

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

! Signal word

Warning

Hazard Statements

- H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

- P102 Keep out of reach of children.
 P261 Avoid breathing vapours/spray.
 P264 Wash hands thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

2,4,6-Tris (dimethylaminomethyl) phenol, 3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

2-component epoxy sticks

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1 < 3	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,5 < 1	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
13463-67-7	236-675-5	titanium-dioxide	1 - 5	



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 23.11.2018 (GB) Version 8.6

Repair Stick Plastic

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
72244-98-5	615-735-8	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	20 - 50	Skin Sens. 1B, H317 / Aquatic Chronic 3, H412

REACH

CAS No	Name	REACH registration number
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	01-2119560597-27
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
13463-67-7	titanium-dioxide	01-2119489379-17
72244-98-5	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	01-2120118957-46

! SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

! In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

! Physician's information / possible symptoms

vomiting

skin irritation

Physician's information / possible dangers

allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

! Unsuitable extinguishing media

Full water jet



Repair Stick Plastic

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Remove persons to safety.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

! Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! General protective measures

Do not inhale vapours.
Avoid contact with eyes and skin

! Hygiene measures

At work do not eat, drink, smoke or take drugs.
Work in rooms with good ventilation.
Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

! Advice on storage compatibility

Do not store together with animal feedstuffs.
Do not store together with food.
Do not store together with acids.
Do not store together with oxidizing agents.

**Repair Stick Plastic****! Further information on storage conditions**

Protect from heat and direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005
13463-67-7	Titanium dioxide: total inhalable dust	8 hours	10		EH40/2005
13463-67-7	Titanium dioxide: respirable dust	8 hours	4		EH40/2005

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
13463-67-7	titanium-dioxide	10 mg/m3	DNEL long-term inhalative (systemic)	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	12,25 mg/m3	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,31 mg/m3	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
13463-67-7	titanium-dioxide	1 mg/l	PNEC aquatic, marine water	
		100 mg/l	PNEC sewage treatment plant (STP)	
		1000 mg/kg	PNEC sediment, marine water	
		100 mg/kg	PNEC sediment, freshwater	
		0,127 mg/l	PNEC aquatic, freshwater	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	11 mg/kg	PNEC Secondary Poisoning	
		0,0996 mg/kg	PNEC sediment, marine water	
		0,018 mg/l	PNEC aquatic, intermittent release	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,996 mg/kg	PNEC sediment, freshwater	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 23.11.2018 (GB) Version 8.6

Repair Stick Plastic**DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,0084 mg/l	PNEC aquatic, marine water	
		0,084 mg/l	PNEC aquatic, freshwater	
		0,2 mg/l	PNEC sewage treatment plant (STP)	

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**! Respiratory protection**

Not required

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

pasty

Colour

blue / white

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	> 35 °C		ca. 101 kPa		
melting point	not applicable				
Flash point	> 100 °C				
Vapourisation rate	not applicable				
Flammable (solid)	not determined				
Flammability (gas)	not determined				

**Repair Stick Plastic**

	Value	Temperature	at	Method	Remark
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 500 Pa	20 °C			
Relative density	ca. 1,8 g/cm ³				
Vapour density	not applicable				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not applicable				
Viscosity kinematic	not applicable				
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Amines

Acid

Oxidising agent, strong

**Repair Stick Plastic****10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	18518 mg/kg			ATE
LD50 acute dermal	1 mg/kg	rat		CAS: 90-72-2
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Experiences made from practice

Sensitization through skin contact possible.

Frequent persistent contact with the skin may cause skin irritation.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

**Repair Stick Plastic****! SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 180 - 240 mg/l (96 h)	Oncorhynchus mykiss		CAS: 90-72-2

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability				not degradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**! General regulation**

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-

**Repair Stick Plastic**

ADR/RID	IMDG	IATA-DGR
14.5. Environmental hazards -	-	-
14.6. Special precautions for user No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable		
Transport/further information No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.