



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product RK 1300 Adhesive
Code-Nr. 105601

1.2. Relevant identified uses of the substance or mixture and uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 2	H225	
Skin Corr. 1A	H314	
Eye Dam. 1		
Skin Sens. 1	H317	
STOT SE 3	H335	

Hazard Statements

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

H335 May cause respiratory irritation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS05



GHS07

Signal word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary Statements

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/eye protection.
P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 Take off contaminated clothing.
P370 + P378 In case of fire: Use foam for extinction.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

2,2'-(4-Methylphenyl) imino]bisethanol, methacrylic acid, methyl methacrylate

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
80-62-6	201-297-1	methyl methacrylate	30 - 50	Flam. Liq. 2, H225 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	>= 0,1 < 1	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
79-41-4	201-204-4	methacrylic acid	3 - 7	Acute Tox. 4, H302, H332 / Acute Tox. 3, H311 / Skin Corr. 1A, H314 / Eye Dam. 1, H318 / STOT SE 3, H335
3077-12-1	221-359-1	2,2'-[(4-Methylphenyl) imino]bisethanol	1 - 3	Acute Tox. 4, H302 / Eye Dam. 1, H318

REACH

CAS No	Name	REACH registration number
80-62-6	methyl methacrylate	01-2119452498-28
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	01-2119560597-27
79-41-4	methacrylic acid	01-2119463884-26
3077-12-1	2,2'-[(4-Methylphenyl) imino]bisethanol	not subject to registration

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In case of inhalation of fumes symptoms of poisoning may occur after hours, medical treatment is necessary.

Seek medical treatment immediately.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Seek medical treatment immediately.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth thoroughly with water.

Give plenty of water to drink in small sips.

4.2. Most important symptoms and effects, both acute and delayed
Physician's information / possible symptoms

Shortness of breath

Allergic symptoms

Skin burns

Gastrointestinal complaints

skin irritation

Physician's information / possible dangers

Risk of allergic-anaphylactic shock

Risk of respiratory disorders



allergic reactions
Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.
Keep under medical supervision for at least 48 hours.
Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Dry powder
Carbon dioxide
Dry sand
water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Metal oxides
Danger of bursting
In case of fire formation of dangerous gases possible.
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.
Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.
Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.



6.3. Methods and material for containment and cleaning up

Dilute with plenty of water.

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr).

After taking up the material dispose according to regulation.

Take up mechanically.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Remove soiled or soaked clothing immediately.

Keep away from food and drink.

Keep away from tobacco.

Wash hands and skin before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

Avoid effect of heat.

Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store together with food.

Do not store together with oxidizing agents.

Do not store together with reducing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from direct solar radiation.

Storage temperature between 2°C to 8°C

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
79-41-4	Methacrylic acid	8 hours	72	20	EH40/2005
		Short-term	143	40	
80-62-6	Methyl methacrylate	8 hours	208	50	EH40/2005
		Short-term	416	100	
80-62-6	Methyl Methacrylate	TWA, 8 hours	208		
		Short-term	416		
79-41-4	methacrylic acid	8 hours	180	50	MAK
		Short-term	360	100	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
80-62-6	methyl-methacrylate	8 hours		50	
		Short-term		100	

DNEL-/PNEC-values
DNEL worker

CAS No	Substance name	Value	Code	Remark
763-69-9	Propionsäure-3-ethoxyethylester	4 mg/m3	DNEL long-term inhalative (systemic)	
79-41-4	methacrylic acid	4,25 mg/kg bw/day	DNEL long-term dermal (systemic)	
		29,6 mg/m3	DNEL long-term inhalative (systemic)	
		88 mg/m3	DNEL long-term inhalative (local)	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,31 mg/m3	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
79-41-4	methacrylic acid	0,82 mg/l	PNEC aquatic, marine water	
		0,82 mg/l	PNEC aquatic, freshwater	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,2 mg/l	PNEC sewage treatment plant (STP)	
		0,084 mg/l	PNEC aquatic, freshwater	
		0,0084 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls
Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Multi-purpose filter ABEK/P3, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.



Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

liquid

Colour

pink

Odour

ester-like

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	> 100 °C				
melting point	not determined				
Flash point	17 °C			closed cup	
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate
Self ignition temperature	430 °C				
Lower explosion limit	2,1 Vol-%				
Upper explosion limit	12,5 Vol-%				
Vapour pressure	< 38 hPa	20 °C			
Relative density	ca. 1 g/cm ³	20 °C			
Vapour density	1	20 °C			
Solubility in water	ca. 16 g/l				partially soluble
Solubility/other	not determined				



	Value	Temperature	at	Method	Remark
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	18000-26000 mPa*s	23 °C			
Viscosity kinematic	not determined				
Solvent content	ca. 50 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions known.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong oxidising agents.

Reactions with reducing agents, heavy metals.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Heavy metal chemical salts

Oxidising agent, strong

Reducing agent

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

Metaloxides

Thermal decomposition

Remark No decomposition below 200°C.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg			ATE
LD50 acute dermal	> 2000 mg/kg			ATE
LC50 acute inhalation	> 20 mg/l (4 h)			ATE
Skin irritation	corrosive			
Eye irritation	risk of strong eye injuries			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Sensitization through skin contact possible.

Causes corrosions.

Risk of strong eye injuries.

Irritates respiratory tract.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 > 79 mg/l (96 h)	Fish	Fisch Early-life Stage Toxicity Test	Toxicology test with the product.
Daphnia	EC50 > 69 mg/l (48 h)	Daphnia magna		Toxicology test with the product.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 26.09.2019

revision 26.09.2019 (GB) Version 8.8

RK 1300 Adhesive

	Value	Species	Method	Validation
Algae	ErC50 45 mg/l (72 h)	Green algae		CAS: 79-41-4
Bacteria	EC50 270 mg/l (17 h)		DIN 38412 T.8	

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	< 94 % (14 d) Toxicology test with the product.			readily degradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

08 04 09*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	2924	2924	2924

**RK 1300 Adhesive**

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methylmethacrylate, Methacrylic acid)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methylmethacrylate, Methacrylic acid)	Flammable liquid, corrosive, n.o.s. (Methylmethacrylate, Methacrylic acid)
14.3. Transport hazard class(es)	3 (8)	3 (8)	3 (8)
14.4. Packing group	II	II	II
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 3+8

tunnel restriction code D/E

Special provisions 274

Classification code FC

Transport/further information

Marine pollutant: NO

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****! VOC standard****VOC content** ca.50 %**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H302,	-?-
H332	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 26.09.2019

revision 26.09.2019 (GB) Version 8.8

RK 1300 Adhesive

- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.