



**! SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Name of product** Spray-on Grease H1  
Code-Nr. 115410

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Recommended intended purpose(s)**

Technical Aerosols

**1.3. Details of the supplier of the safety data sheet**

**Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories      Hazard Statements      Classification procedure

**Aerosol 1**      **H222, H229**

**Hazard Statements**

H222      Extremely flammable aerosol.  
H229      Pressurised container: May burst if heated.

**2.2. Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS02

**Signal word**

Danger

**Hazard Statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**Precautionary Statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container to hazardous or special waste collection point.

**2.3. Other hazards****Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Preparation of metallic soap in synthesis oil with additives

Mixture of active ingredients with propellant

**Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
61641-74-5		propane/butane-mixture	60 - 70	Flam. Gas 1, H220 / Press Gas, H280

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.



## Spray-on Grease H1

### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

### In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## ! SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

#### ! Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## ! SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

### 6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

**Spray-on Grease H1****6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****! Advice on safe handling**

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Do not inhale aerosols

**Hygiene measures**

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Further information on storage conditions**

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

**Spray-on Grease H1****Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

aerosol

**Colour**

yellowish-white

**Odour**

like mineral oil

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not applicable				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	not applicable				Aerosol
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	> 250 °C				
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	0,6 Vol-%				
<b>Upper explosion limit</b>	3,2 Vol-%				
<b>Vapour pressure</b>	3,5 bar	20 °C			Doseninnendruck
<b>Relative density</b>	0,72 g/ml	20 °C			
<b>Vapour density</b>	not determined				

**Spray-on Grease H1**

	Value	Temperature	at	Method	Remark
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	not determined				
<b>Solids content</b>	29,1 %				

**Oxidising properties**

No information available.

**Explosive properties**

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

**9.2. Other information**

No information available.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

Keep away from heat.

Formation of explosive gas/air mixtures.

**10.5. Incompatible materials****! Substances to avoid**

Reactions with oxygen.

**10.6. Hazardous decomposition products**

Sulphurous oxides (SOx)

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>Skin irritation</b>	low irritant effect - not necessary to label			
<b>Eye irritation</b>	low irritant - no labeling duty			

**Spray-on Grease H1**

	Value/Validation	Species	Method	Remark
<b>Skin sensitization</b>	non-sensitizing			

**Experiences made from practice**

Vapours may cause dizziness, headaches and tiredness

According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

**! Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

**SECTION 12: Ecological information****12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

Elimination rate

Method of analysis

Method

Validation

**Biological degradability**

The product is slightly degradable.

**12.3. Bioaccumulative potential**

No information available.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

**! SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

15 01 10\*

**Name of waste**

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

**! General information**

For proper waste disposal a complete emptying of the tin is necessary.

**Spray-on Grease H1****! SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	1950	1950	1950
<b>14.2. UN proper shipping name</b>	AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4. Packing group</b>	-	-	-
<b>14.5. Environmental hazards</b>	No	No	No

**14.6. Special precautions for user**

Caution: Gases

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 62,8 %**VOC value** 399,8 g/L**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**! SECTION 16: Other information****! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.