

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Top-Lube-Fluid-Spray
Code-Nr. 115120

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Skin Irrit. 2	H315	
STOT SE 3	H336	
Aquatic Chronic 3	H412	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapours/spray.
 P264 Wash hands thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 Take off contaminated clothing.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, pentane

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

3.2. Mixtures**Description**

Mixture of active ingredients with propellant

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
74-98-6	200-827-9	propane	2,5 < 10	Flam. Gas 1, H220 / Press. Gas
109-66-0	203-692-4	pentane	10 < 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
92128-66-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	10 < 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
106-97-8	203-448-7	Butan (1,3 Butadiene <0,1%)	25 < 50	Flam. Gas 1, H220 / Press. Gas, H280
68411-46-1	270-128-1	Alkylated Diphenylamines	1 < 2,5	Aquatic Chronic 3, H412

REACH

CAS No	Name	REACH registration number
74-98-6	propane	01-2119486944-21
109-66-0	pentane	01-2119459286-30
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	01-2119475514-35-xxxx
106-97-8	Butan (1,3 Butadiene <0,1%)	01-2119474691-32
68411-46-1	Alkylated Diphenylamines	01-2119491299-23

! SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed**! Physician's information / possible symptoms**

Headache

Confusion

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

High risk of slipping due to leakage/spillage of product.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into surface waters/groundwater.

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Ventilate area concerned

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Ensure sufficient ventilation.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**! Requirements for storage rooms and vessels**

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

! Further information on storage conditions

Store only in original container at temperature of 40°C maximum (=104°F).

Keep container tightly closed, open and handle carefully.

Protect from heat and direct solar radiation.

Keep container dry, tightly closed and store at cool and aired place.

Protect from heat/overheating.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 12.12.2017 (GB) Version 1.4

Top-Lube-Fluid-Spray**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0	pentane	8 hours	3000	1000	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
109-66-0	pentane	432 mg/kg	DNEL long-term dermal (systemic)	
		3003 mg/m3	DNEL long-term inhalative (systemic)	
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	2035 mg/m3	DNEL long-term inhalative (systemic)	
		773 mg/kg bw/day	DNEL long-term dermal (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

yellowish

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	-44 °C				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 12.12.2017 (GB) Version 1.4

Top-Lube-Fluid-Spray

	Value	Temperature	at	Method	Remark
melting point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not applicable				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	> 200 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,8 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	2100 hPa	20 °C			
Relative density	0,767 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	50 %				
Oxidising properties	No information available.				
Explosive properties	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
9.2. Other information	No information available.				

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products**Thermal decomposition**

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5840 mg/kg	rat		CAS: 64742-49-0
LD50 acute dermal	> 2920 mg/kg	rabbit		CAS: 64742-49-0
LC50 acute inhalation	> 25 mg/l (4 h)	rat		CAS: 64742-49-0
Skin irritation	irritant			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

Experiences made from practice

Frequent persistent contact with the skin may cause skin irritation.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 4,26 mg/l (96 h)	Oncorhynchus mykiss		CAS: 109-66-0
Daphnia	NOEC 0,17 mg/l (21 d)	Daphnia magna		CAS: 64742-49-0
Algae	NOELR 3 mg/l (72 h)	Pseudokirchneriella subcapitata		CAS: 64742-49-0

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Harmful to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 12.12.2017 (GB) Version 1.4

Top-Lube-Fluid-Spray

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Land and inland navigation transport ADR/RID	Hazard label(s) 2.1 tunnel restriction code D Classification code 5F		
! Transport/further information	Marine pollutant: NO		

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content	50 %
VOC value	383,5 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL-code: 5-3

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.3

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 12.12.2017 (GB) Version 1.4

Top-Lube-Fluid-Spray

H412 Harmful to aquatic life with long lasting effects.